

## County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 9, T. 29 S., R. 3 W.

CHAINS

A fir, 12 ins. diam., bears N. 75° E., 39½ lks.  
dist., mkd. C¼ S9 BT.

A cedar, 16 ins. diam., bears S. 63° W., 112 lks.  
dist., mkd. C¼ S9 BT.

Ascend 60 ft. over SW. slope.

44.25 Gravelled road, 20 lks. wide, bears N. 20°W. and S. 20° E.

50.60 Top of ascent, slopes W.; desc. 15 ft. over NW. slope.

52.90 Creek, 1 lk. wide, course S. 70°W.; asc. 155 ft. over  
SW. slope.

68.20 Spur, slopes W.; desc. 100 ft. over NW. slope.

73.45 Creek, 2 lks. wide, course SW.; asc. 140 ft. over SE. slope.

78.36 The ¼ sec. cor. of secs. 4 and 9.

From the ¼ sec. cor. of secs. 9 and 10.

N. 89° 54' W., on the E. and W. center line of sec. 9.

Ascend 140 ft. over SE. slope, through heavy timber and  
dense undergrowth.

7.60 Ridge, bears N. and S.; desc. 355 ft. over NW. slope.

24.85 Ravine, drains SW.; asc. 35 ft. over SE. slope.

29.70 Top of ascent, slopes S.; desc. 210 ft. over SW. slope.

30.50 Leave timber, enter logged area; continue through scattering  
timber and dense undergrowth.

38.80 Gravelled road, 20 lks. wide, bears N. and S.

40.36 The center ¼ sec. cor. of sec. 9.

Descend 5 ft. over SW. slope.

42.40 Weaver Creek, 15 lks. wide, course S.; asc. 255 ft. over E.  
slope, changing to NE. slope.

60.36 Point for the center W 1/16 sec. cor. of sec. 9.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in  
the ground, with brass cap mkd.

$$\begin{array}{c} C \quad W \quad 1/16 \quad C \\ \quad \quad S \quad 9 \\ \quad \quad 1966 \end{array}$$

from which

A fir, 8 ins. diam., bears N. 30½° E., 30 lks.  
dist., mkd. CW 1/16 S9 BT.

A hemlock, 8 ins. diam., bears S. 74°E., 18 lks.  
dist., mkd. CW 1/16 S9 BT.

Ascend 70 ft. over NE. slope.

65.20 Spur, slopes N. 30°E.; desc. 45 ft. over NW. slope.