

County Surveyor's Record, Douglas County, Oregon

Subdivision of Sec. 33, T. 29 S., R. 3 W.

CHAINS	
6.45	Ravine, drains N. 60° W.; desc. 50 ft. over NW. slope, changing to N. slope.
9.10	Creek, 2 lks. wide, course N. 60° W.; asc. 30 ft. over SW. slope.
10.80	Top of ascent, slopes NW.; desc. 25 ft. over NW. slope.
11.95	Ravine, drains W.; asc. 110 ft. over SW. slope.
17.20	Top of ascent, slopes SW.; desc. 30 ft. over NW. slope.
20.06	Point for the center S 1/16 sec. cor. of sec. 33.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \text{C} \\ \text{S } 1/16 \text{ S } 33 \\ \text{C} \\ 1967 \end{array}$
	from which
	A fir, 58 ins. diam, bears S. 35¼° E., 94 lks. dist., mkd. CS 1/16 S33 BT.
	A fir, 21 ins. diam., bears S. 26° W., 178 lks. dist., mkd. CS 1/16 S33 BT.
	The corner is located at the SE. cor. of logged area, edge bears N. and W.
	Descend 30 ft. over NW. slope.
20.85	Wet ravine, drains S. 60° W.; asc. 110 ft. over S. slope, changing to SW. slope.
23.90	Spur, slopes S. 70° W.; desc. 265 ft. over NW. slope.
33.75	Days Creek Road, asphaltic surface, 30 lks. wide, bears N. 20° E. and S. 20° W., enter creek bottom; desc. 2 ft. over creek bottom through scattering young timber.
34.43	Wire fence, bears N. 20° E. and S. 20° W.
40.12	Point for the center ¼ sec. cor. of sec. 33, at intersection with the E. and W. center line.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \text{C } 1/4 \text{ S } 33 \\ 1967 \end{array}$
	from which
	A fir, 11 ins. diam., bears N. 44° E., 82 lks. dist., mkd. C ¼ S33 BT.
	A fir, 12 ins. diam., bears S. 0½° E., 60 lks. dist., mkd. C ¼ S33 BT.
	Descend 3 ft. over creek bottom.
40.80	Cut bank of Days Creek, edge bears NE., curving to N., and SW.; desc. 4 ft. over rocky creek bottom.
42.00	Days Creek, in a bend, 5 lks. wide, course SW., curving