

Subdivision of Sec. 33, T. 29 S., R. 3 W.

CHAINS	
45.60	Same creek, course S. 30°W., curving to S.; asc. 5 ft. over creek bottom.
47.03	Wire fence, bears N. 20° E. and S. 20° W.
49.70	Power and telephone line, bears N. 20° E. and S. 20°W.
52.40	Leave creek bottom, edge bears NE. and SW.; asc. 60 ft. over SE. slope, through heavy timber.
57.50	Top of ascent, slopes SE.; desc. 5 ft. over NE. slope.
60.28	Point for the center N 1/16 sec. cor. of sec. 33. Set an iron post, 28 ins. long, 2½ ins. diam., the top 2 ins. below the surface of a road, with brass cap mkd.
	$\begin{array}{c} G \\ N \ 1/16 \ S \ 33 \\ G \\ 1967 \end{array}$
	from which
	A fir, 30 ins. diam., bears S. 70½° E., 69lks. dist., mkd. CN 1/16 S33 BT.
	A fir, 30 ins. diam., bears S. 78½°W., 56 lks. dist., mkd. CN 1/16 S33 BT.
	The corner falls in the center of a gravelled road, 15 lks. wide, bears N. 10°W. and S. 10°E.
	Descend 15 ft. over NE. slope.
65.25	Ravine, drains S. 60° E.; asc. 70 ft. over S. slope, changing to SE. slope.
66.20	Abandoned dirt road, 15 lks. wide, bears N. 60° W. and S. 60° E.
68.35	Wire fence, bears N. 20° W. and S. 20° E.; enter logged area.
70.30	Spur, slopes SE.; desc 40 ft. over NE. slope.
74.60	Wire fence, bears N. 30° E. and S 10°W.
75.70	Power and telephone line, bears N. 60° W. and S. 60° E.
77.40	Bottom of descent, drains S. 60° E.; asc. 40 ft. over S. slope.
80.44	The ¼ sec. cor. of secs. 28 and 33.
	From the ¼ sec. cor. of secs. 33 and 34.
	N. 89° 54' W., on the E. and W. center line of sec. 33.
	Descend 345 ft. over SW. slope, changing to W. slope, across logged area, through scattering timber and dense undergrowth.
2.40	Abandoned dirt road, 15 lks. wide, bears N. and S., curving to SE.