

Subdivision of Sec. 33, T. 29 S., R. 3 W.

CHAINS	
5.70	Newly constructed gravelled road, 30 lks. wide, bears N. 10° W. and S. 10° W., curving to S.
10.45	Creek, 2 lks. wide, course N. 25° W.; asc. 95 ft. over NE. slope.
15.25	Spur, slopes NW.; desc. 125 ft. over NW. slope.
19.70	Point for the center E 1/16 sec. cor. of sec. 33. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} C \quad E \ 1/16 \quad C \\ \hline S \ 33 \\ 1967 \end{array}$
	from which
	A white fir, 12 ins. diam., bears N. 73 3/4°W., 55 lks. dist., mkd. CE 1/16 S33 BT.
	A fir, 8 ins. diam., bears S. 78° W., 39 lks. dist., mkd. CE 1/16 S33 BT.
	Descend 5 ft; over NW. slope.
19.95	Creek, 2 lks. wide, course N. 25° W.; asc. 90 ft. over NE. slope.
24.85	Spur, slopes N.; desc. 175 ft. over NW. slope.
30.95	Dry bed of creek, 1 lk. wide, course N., curving to NW.; desc. 65 ft. over NW. slope, changing to W. slope.
35.75	Days Creek Road, asphaltic surface, 30 lks. wide, bears N. 20° E. and S. 20° W.
37.20	Gravelled road, 15 lks. wide, bears N. and S., enter creek bottom; desc. 10 ft. over gradual W. slope, through scattering young timber.
37.40	Wire fence, bears N. and S.
39.40	The center ¼ sec. cor. of sec. 33. Descend 5 ft. over creek bottom.
40.00	Cut bank of Days Creek, edge bears NE. and SW., curving to W.; continue over rocky creek bottom.
41.00	Same cut bank, edge bears NW., curving to W., and SE.; desc. 10 ft. over creek bottom.
43.50	Days Creek, 15 lks. wide, course S., curving to SW.; asc. 80 ft. over SE. slope.
48.00	Power and telephone line, bears N. 50° E. and S. 50° W.
52.20	Top of ascent, slopes S.; desc. 80 ft. over SW. slope.
58.25	May Creek, 8 lks. wide, course S. 35°E.; asc. 25 ft. over SE. slope.
59.58	Point for the center W 1/16 sec. cor. of sec. 33. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.