

Subdivision of Sec. 33, T. 29 S., R. 3 W.

CHAINS

C  $\frac{W 1/16}{S 33}$  C  
1967

from which

A fir, 10 ins. diam., bears N.  $50\frac{1}{2}^{\circ}$  W., 95 $\frac{1}{2}$  lks.  
dist., mkd. CW 1/16 S33 BT.

A fir, 6 ins. diam., bears S.  $39\frac{1}{2}^{\circ}$  W., 49 $\frac{1}{2}$  lks.  
dist., mkd. CW 1/16 S33 BT.

Ascend 210 ft. over SE. slope.

65.60 Spur, slopes S.  $35^{\circ}$ E.; desc. 80 ft. over SW. slope.67.10 Wire fence, bears N.  $15^{\circ}$ E. and SW.69.95 Bottom of descent, drains S., and dirt road, 15 lks.  
wide, bears N. and S.; asc. 220 ft. over SE. slope.79.76 The  $\frac{1}{4}$  sec. cor. of secs. 32 and 33.

---

 From the center E 1/16 sec. cor. of sec. 33.

N.  $1^{\circ} 47'$  E., on the N. and S. center line of the NE  $\frac{1}{4}$   
of sec. 33.

Descend 85 ft. over NW. slope, across logged area, through  
scattering timber and dense undergrowth.

8.60 Creek, 3 lks. wide, course N.  $85^{\circ}$  W.; asc. 50 ft. over  
SW. slope.10.45 Newly constructed gravelled road, 30 lks. wide, bears N.  
 $75^{\circ}$  W. and S.  $55^{\circ}$  E.11.85 Abandoned dirt road, 20 lks. wide, bears N.  $80^{\circ}$  W. and  
S.  $80^{\circ}$  E.

13.00 Top of ascent, slopes W.; desc. 25 ft. along w. slope.

19.50 Wire fence, bears E. and W.

20.31 Point for the NE 1/16 sec. cor. of sec. 33, at intersection  
with the E. and W. center line of the NE  $\frac{1}{4}$ .

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 2 $\frac{1}{2}$  ins.  
in the ground, with brass cap mkd.

NE 1/16 S 33  
1967

from which

A fir, 15 ins. diam., bears N.  $42^{\circ}$ E., 48 lks.  
dist., mkd. NE 1/16 S33 BT.

A fir, 52 ins. diam., bears S.  $61\frac{1}{2}^{\circ}$ W., 88 lks.  
dist., mkd. NE 1/16 S33 BT.

Descend 65 ft. over NW. slope.

26.15 Gravelled road, 30 lks. wide, bears N.  $40^{\circ}$ E. and  
S.  $30^{\circ}$ W.26.95 Wire fence, bears N.  $40^{\circ}$ E. and S.  $40^{\circ}$ W.; enter pasture.