

County Surveyor's Record, Douglas County, Oregon

Subdivision of Sec. 33, T. 29 S., R. 3 W.

CHAINS	
31.00	Enter open creek bottom, edge bears NE. and SW.
37.00	Wire fence, bears N. 25° E. and S. 25° W.; enter cultivated field.
40.65	The E 1/16 sec. cor. of secs. 28 and 33.
<hr/>	
	From the N 1/16 sec. cor. of secs. 33 and 34.
	S. 89° 40' W., on the E. and W. center line of the NE 1/4 of sec. 33.
	Ascend 5 ft. over NE. slope, across logged area, through scattering timber and light undergrowth.
0.80	Spur, slopes N. 20° W.; desc. 75 ft. over broken SW. slope.
8.40	Spur, slopes S. 50° W., and enter heavy timber, edge bears N. 50° E. and S. 50° W.; desc. 350 ft. over NW. slope.
18.10	Wire fence, bears N. and S.; enter logged area.
20.06	The NE 1/16 sec. cor. of sec. 33.
	Descend 90 ft. over NW. slope.
23.75	Gravelled road, 25 lks. wide, bears N. 25° E. and S. 10° W.
24.15	The corner of wire fences extending N. 15° E., S. 80° E., and SW.
36.00	Enter creek bottom, edge bears N. 15° E. and S. 15° W.; continue over nearly level creek bottom.
30.50	Private gravelled road, 15 lks. wide, bears N. 25° W. and S. 25° E.
32.25	Cut bank of Days Creek, bears NW. and S. 25° E.; desc. 7 ft. over rocky creek bottom.
32.40	Days Creek, 10 lks. wide, course S. 20° E.; asc. 7 ft. over rocky creek bottom.
34.25	Cut bank of creek, bears N. 15° W. and S. 65° E.; asc. 50 ft. over E. slope.
35.80	Power and telephone line, bears N. 20° E. and S. 20° W.
39.30	Wire fence, bears N. and S.; enter heavy timber.
40.12	The center N 1/16 sec. cor. of sec. 33.
<hr/>	
	From the W 1/16 sec. cor. of sec. 33 only, on the S. bdy. of the Tp.
	N. 0° 23' E., on the N. and S. center line of the SW 1/4 of sec. 33.
	Ascend 1 ft. along W. slope, through medium timber and dense undergrowth.
1.10	Top of ascent, slopes W.; desc. 220 ft. over NW. slope.
11.95	Days Creek Road, asphaltic surface, 30 lks. wide, bears