

Subdivision of Sec. 33, T. 29 S., R. 3 W.

CHAINS	
15.62	<p>Point selected for a witness point.</p> <p>Set a fiberglass post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W P S 33 1967</p>
	<p>Descend 20 ft. over W. slope.</p>
18.90	<p>Leave cultivated field at cut bank of Days Creek, edge bears N. 25° W. and S., curving to SW.; desc. 10 ft. over rocky creek bottom.</p>
19.80	<p>Days Creek, in a bend, 10 lks. wide, course S., curving to W., from NW.; continue along creek.</p>
20.02	<p>The SW 1/16 sec. cor. of sec. 33.</p> <p>Ascend 5 ft. over creek bank.</p>
20.17	<p>Cut bank of creek, bears NW. and S., curving to SW.; continue over nearly level creek bottom through timber and undergrowth.</p>
21.02	<p>Point selected for a witness cor. to the SW. 1/16 sec. cor. of sec. 33.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W C SW 1/16 S 33 —————> 1967</p>
	<p>from which</p> <p style="padding-left: 40px;">An ash, 21 ins. diam., bears N. 81½° W., 86 lks. dist., mkd. with an X at breast height and BT at base.</p> <p style="padding-left: 40px;">An ash, 12 ins. diam., bears S. 52½° E., 53 lks. dist., mkd. with an X at breast height and BT at base.</p>
	<p>Continue over nearly level creek bottom.</p>
25.15	<p>Leave timber and creek bottom, edge bears N. 40° E. and S. 40° W.; asc. 140 ft. over SE. slope, through open pasture.</p>
27.25	<p>Power and telephone line, bears N. 25° E. and S. 25° W.</p>
28.75	<p>Private gravelled road, 15 lks. wide, bears N. 10° E. and S. 10° W.</p>
36.03	<p>Wire fence, bears N. 35° E. and S. 35° W.</p>
38.80	<p>Creek, 1 lk. wide, course S., curving to SE.; asc. 10 ft. over SE. slope of swampy area.</p>
39.55	<p>Spring seepage, drains S., curving to SE. ; asc. 10 ft. over E. slope.</p>
40.05	<p>The S 1/16 sec. cor. of secs. 32 and 33.</p>