

T. 30 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

The history of surveys of township 30 south, range 3 west, Willamette Meridian, Oregon, in the portion covered by this resurvey is as follows:

A portion of the subdivisional lines were surveyed by William M. Bushey in 1893 as shown on the official plat of survey approved June 29, 1895.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions, except for the closing corner of sections 3 and 4 which was established at intersection with the south boundary of township 29 south, range 3 west. The retracement data were thoroughly verified and only the true line field notes are given herein. All lines were measured twice and blazed.

The resurvey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and Special Instructions dated August 25, 1965, and Supplemental Special Instructions dated October 24, 1967, under Group 599, Oregon.

The directions of lines were determined by the solar transit method.

The geographic position of the corner of sections 3, 4, 9, and 10, as scaled from the Days Creek quadrangle map, published by the United States Geological Survey in 1954, is as follows:

Latitude 42° 59.4' N. Longitude 123° 03.6' W.

The mean magnetic declination is 18° 15' East.

Dependent Resurvey, Line Between Sections 3 and 4,
T. 30 S., R. 3 W., Willamette Meridian, Oregon

(Restoring the 1893 survey by William M. Bushey)

The cor. of secs. 3, 4, 9, and 10, monumented with the original conglomerate stone, 9 x 8 x 5 ins., firmly set 4 ins. in the ground, mkd. with 3 grooves on E. and 5 notches on the S. edge, from which the remaining original bearing trees:

A sawed fir stump, 35 ins. diam., bears
S. 85° W., 93½ lks. dist., with a healed
blaze. (Record, S. 83½° W.)

A fir, 52 ins. diam., bears N. 64½° W.,
56 lks. dist., with illegible scribe marks
visible on partially opened blaze. (Record,
N. 66¼° W.)

and bearing trees mkd. by R. H. Gee, Registered Logging
Engineer, No. 3723, in 1956

A fir, 30 ins. diam., bears N. 35° E., 56½ lks.
dist., with a healed blaze.

A madrone, 13 ins. diam., bears S. 61° E.,
70 lks. dist., with scribe marks S10 BT
visible on partially healed blaze.

At the corner point