

Dependent Resurvey, Line Bet. Secs. 3 and 4, T. 30 S., R. 3 W.

CHAINS

T 29 S R 3 W
 $\frac{S 33}{S 4/S 3}$
 C C
 T 30 S R 3 W
 1967

from which

A fir, 18 ins. diam., bears S. $49 \frac{3}{4}^\circ$ E., 30 lks. dist., with illegible scribe marks visible on partially healed blaze. (This tree is the original SE. bearing tree)

A fir, 12 ins. diam., bears S. $56 \frac{1}{4}^\circ$ W., $60 \frac{1}{2}$ lks. dist., with a healed blaze. (This tree was mkd. by R. H. Gee, Registered Logging Engineer No. 3723, in 1955)

From this point the original closing cor. of secs. 3 and 4, bears N. $0^\circ 26'$ E., 0.075 chs. dist., monumented with the original conglomerate stone, 16 x 10 x 10 ins., firmly set 10 ins. in the ground, mkd. with 3 notches on the E. and W. faces, and CC on the S. face, from which the original bearing trees:

A fir snag, 16 ins. diam., bears N. $24 \frac{1}{4}^\circ$ E., $12 \frac{3}{4}$ lks. dist., with scribe marks T30S R3W visible on partially healed blaze.

A fir, 18 ins. diam., bears S. $39 \frac{1}{4}^\circ$ E., $35 \frac{1}{2}$ lks. dist., with illegible scribe marks visible on partially healed blaze.

A madrone stump hole and clump of madrone sprouts, bears S. $17 \frac{1}{4}^\circ$ W., 39 lks. dist.

and a bearing tree mkd. by R. H. Gee, Registered Logging Engineer, No. 3723, in 1955

A fir, 12 ins. diam., bears S. 51° W., $65 \frac{1}{2}$ lks. dist., with a healed blaze.

From this same point the cor. of secs. 33 and 34, on the S. bdy. of T. 29 S., R. 3 W., bears S. $89^\circ 32'$ E., 2.785 chs. dist., monumented with an iron post, $2 \frac{1}{2}$ ins. diam., firmly set, mkd. and witnessed as described in the field notes of the 1967 dependent resurvey of a portion of the S. bdy. of T. 29 S., R. 3 W.

Land, mountainous.

Soil, rocky clay.

Timber, fir, madrone, dogwood, chinquapin, yew, cedar, and maple; undergrowth, fern, salal, vine maple, hazel, arrowwood, and timber reproduction.

GENERAL DESCRIPTION

The line between sections 3 and 4 is located about $5 \frac{1}{2}$ miles northeast of Days Creek, Oregon. Elevation ranges from about 2000 feet at the closing corner of sections 3 and 4, to about 2700 feet above sea level on the main ridge dividing Days Creek and St. John Creek drainage. This main ridge leads from Bland Mountain which is located about 3 miles to the southwest and provides the only access road to the line resurveyed.