

# County Surveyor's Record, Douglas County, Oregon

14669

HOMESTEAD ENTRY SURVEY NO. 186 SECS. 21 & 28 T 32 S R 3 W

CHAINS

(added 7/28/75)

- from which -

A fir 26 ins. dia. bears N.12°02'W., 36 lks. dist. mkd. X 11 HES 186 BT.

A fir, 28 ins. Bears N.83°32'W., 31 lks. dist. mkd. X 11 HES 186 BT.  
 Raise a mound of earth 4 ft. base, 2 ft. high, 3-1/2 ft. dist. within the claim.

September 12, 1916: At the above mentioned cor. I set off 4°06'N. on the decl. arc, and at 11<sup>h</sup>56<sup>m</sup> 1.m.t., obs. the sun on the mer.; the resulting lat. is 42°46'N.

Thence I run: S.58°30'W. on a true line, along west side of road exemption.

Through fir and alder timber and undergrowth.

9.17 Pass to unlisted land.

17.47 Cor. No. 12.

Set a granite stone 24x10x5 ins., 14 ins. in the ground, over a stone mkd. with a cross for cor. No. 12 of this survey, mkd. 12 HES 186 on side facing the claim:

- from which -

A fir 40 ins. dia. bears N.30°15'W. 21 lks. dist., mkd. X 12 HES 186 BT.

A fir 16 ins. dia. bears N.22°30'E., 64 lks. dist., mkd. X 12 HES 186 BT.

Raise a mound of earth 4 ft. base, 2 ft. high, 3-1/2 ft. dist. within the claim.

Cor. No. 7 of Tract A bears S.41°30'W., 1.37 chs. dist.

Thence I run: N.41°30'E. on a true line, along west bdy. of unlisted tract.

Through dense undergrowth and fir and alder timber; SE. slope.

22.40 Draw, course SE.

37.46 Cor. No. 13, on line bet. cors. 4 and 5, List 6-422 (Retracement herinafter described).

Set a diorite stone 24x18x7 ins., 14 ins. in the ground, over a stone mkd. with a cross for cor. No. 13 of this survey, mkd. 13 HES 186 on side facing the claim;

- from which -

A fir 30 ins. dia. bears S.22°00'W. 77 lks. dist. mkd. X 13 HES 186 BT.

A fir 18 ins. dia. bears N.75°40'E., 60 lks. dist., mkd. X 13 HES 186 BT.

Raise a mound of earth 4 ft. base, 2 ft. high, 3-1/2 ft. dist. within the claim.