

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Part of the South Boundary of
T. 29 S., R. 1 E.

CHAINS
9.00

Spur, slopes SE.; asc. 130 ft. over SE. slope.

16.75

Ridgem bears N.30°W.; desc. 185 ft. over NW.
slope, changing to SW. slope.

27.84

Branch, 2 lks. wide, course S.; asc. 123 ft. over E. slope.

37.10

spur, slopes S., desc. 63 ft. over W. slope.

39.98

The original $\frac{1}{4}$ sec. cor. of secs. 2 and 35, which is a
basalt stone, 15x9x4 ins., firmly set, mkd. $\frac{1}{4}$ on N.
face. Hereafter this cor. will refer to sec. 35 only.

At point for corner,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the
ground, with the original stone deposited at the base,
for the $\frac{1}{4}$ sec. cor. of sec. 35 only, with brass cap mkd.

$\frac{1}{4}$ S 35

1937

from which

A fir, 15 ins. diam., bears N.55°E., 32 lks. dist.,
blaze healed; I do not open. (Old B.T.)

A fir, 11 ins. diam., bears S.81°E., 20 lks. dist.,
mkd. $\frac{1}{4}$ S 2 B T. I obliterate the marks on this
tree. (Old B.T.)

A fir, 11 ins. diam., bears N.38°W., 56 lks. dist.,
mkd. $\frac{1}{4}$ S 35 B T. (New B.T.)

Thence

N.89° 55' W., continuing measurements.

Desc 100 ft. over NW.slope.

44.56

Luck creek, 3lks. wide, course S.15°W.; asc. 285 ft. over
E. slope.

59.30

Spur, slopes S.30°W., desc. 40 ft. over SW. slope.

69.17

Spring branch, 1 lk. wide, source S.; asc. 135 ft. over
SE. slope.

79.96

The original cor. of secs 2, 3, 34, which is a
basalt stone, 18x12x6 ins., firmly set, mkd. with 2
notches on E. and 4 notches on W. edge. Hereafter this
cor. will refer to secs. 34 and 35 only.

At point for corner,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the
ground, with the original stone deposited at the base,
for cor. of secs. 34 and 35 only, with brass cap ,kd.

T29S R1E.

S34|S35

T30S R1E

S 3

1937

from which

A pine, 28 ins. diam., bears N. 76°E., 13 lks. dist.,
blaze healed; I do not open. (Old B.T.)