

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Part of the South Boundary of
T. 29 S., R. 1 E.

CHAINS	<p>A pine, 45 ins. diam., bears S. 57°E., 40 lks. dist., mkd. T 30 S R 1 E S 2 B T. I obliterate the marks on this tree. (Old B.T.)</p> <p>A madrona, 11 ins. diam., bears S. 57°W., 46 lks. dist., mkd. T 30 S R 1 E S 3 B T. I obliterate the blaze healed; I do not open. (Old B.T.)</p> <p>A fir, 33 ins. bears N. 84°W., 50 lks. blaze healed; I do not open (Old B.T.)</p> <p>Soil, sandy clay; 3rd rate. Land, mountainous. Timber, fir, pine, madrona, oak, cedar, hemlock, and yew. Undergrowth, vinemaple, serviceberry, 2nd growth, hazel, spirea, and willow.</p>
	<p>N. 89° 51' W., along S. bdy. of sec. 34.</p> <p>Asc. 290 ft. over SE. slope, changing to E. slope, through heavy timber and dense undergrowth.</p>
11.40	<p>Spur, slopes S. 30°E.; desc. 80 ft. over SW. slope.</p>
19.60	<p>draw, drains S. 30°E.; asc. 115 ft. over E. slope.</p>
27.60	<p>Spur, slopes SW. from N., desc. 200 ft. over W. slope.</p>
39.81	<p>The original $\frac{1}{4}$ sec. cor. of secs. 3 and 34, which is a conglomerate stone, 10x6x4 ins., firmly set, mkd. $\frac{1}{4}$ on N. face. Hereafter this cor. will refer to sec. 34 only.</p>
	<p>At point for corner,</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the original stone deposited at the base, for the $\frac{1}{4}$ sec. cor. of sec. 34 only, with brass cap mkd. <u>$\frac{1}{4}$ S 34</u></p>
	1937
	from which
	<p>A fir, 45 ins. diam., bears N. 48°W., 20 lks. dist., blaze healed; I do not open. (Old B.T.)</p>
	<p>A madrona, 13 ins. diam., bears S. 44°W., 22 lks. dist., mkd. $\frac{1}{4}$ S 3 B T. I obliterate the marks on this tree. (Old B.T.)</p>
	<p>A pine, 28 ins. diam., bears N. 28$\frac{1}{4}$°E., 99 lks. dist., mkd. $\frac{1}{4}$ S 34 B T.</p>
	Thence
	<p>N. 89° 58' W., continuing measurements.</p>
	<p>Desc. 420 ft. over broken W. slope.</p>
71.00	<p>North and South Trail, bears NW. and SE.</p>
74.50	<p>Tallow Creek, 3 lks. wide, course S. 15°E., asc. 155 ft. over E. slope.</p>
76.00	<p>North and South Trail, bears N. 15°E. and S. 15°W.</p>
78.22	<p>The closing cor. of secs. 3 and 4, which is a conglomerate stone, 20x10x10 ins., firmly set, mkd. with 3 grooves on E., C C on S., and 3 grooves on W. face.</p>
	<p>At point for corner,</p>