

## County Surveyor's Record, Douglas County, Oregon

Subdivision of Part of T. 30 S., R. 1 E.

CHAINS	
1.70	Top of ascent on E. slope; enter heavy timber, bears NE. and SW.; desc. 625 ft. over NE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ \text{S26}   \text{S25} \\ 1937 \end{array}$ <p style="text-align: right;">from which</p> <p>A fir, 8 ins. diam., bears S.50°E., 59 lks. dist., mkd. <math>\frac{1}{4}</math> S 25 B T.</p> <p>A fir, 40 ins. diam., bears S.46°W., 48 lks. dist., mkd. <math>\frac{1}{4}</math> S 26 B T.</p> <p>Desc. 270 ft. over NE. slope.</p>
51.20	Spring branch, 1 lk. wide, course S.85°E.; asc. 155 ft. over SE slope.
61.25	Top of ascent on E. slope; desc. 400 ft. over NE. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 23, 24, 25, and 26, with brass cap mkd. $\begin{array}{c} \text{T30S R1E} \\ \text{S23}   \text{S24} \\ \text{S26}   \text{S25} \\ 1937 \end{array}$ <p style="text-align: right;">from which</p> <p>A fir, 15 ins. diam., bears N.35°E., 119 lks. dist., mkd. T 30 S R 1 E S 24 B T.</p> <p>A fir, 13 ins. diam., bears S.44°E., 11 lks. dist., mkd. T 30 S R 1 E S 25 B T.</p> <p>A fir, 25 ins. diam., bears S.53°W., 65 lks. dist., mkd. T 30 S R 1 E S 26 B T.</p> <p>A fir, 38 ins. diam., bears N.27°W., 54 lks. dist., mkd. T 30 S R 1 E S 23 B T.</p> <p>Land, mountainous.  Soil, sandy clay and rocky; 2nd and 4th rate.  Timber, fir, hemlock, pine, cedar, and yew.  Undergrowth, rhododendron, vinemaple, chinquapin, 2nd growth, huckleberry, and salal.</p> <hr/> <p>N.89° 57' W., on a random line bet. secs. 23 and 26.</p>
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.20	Intersect N. and S. line, 9 lks. S. of cor. of secs. 22, 23, 26, and 27, <p>Thence  S.89°53' E., on true line ber. secs. 23 and 26.</p>
40.10	Desc. 820 ft. over E. slope, changing to SE. slope, through heavy timber and dense undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.