

# 14095 County Surveyor's Record, Douglas County, Oregon

Subdivision of Part of T.30 S., R. 1 E.

CHAINS

A yellow pine, 42 ins. diam., bears N.20°E., 83 lks. dist., mkd. T 30 S R 1 E S 13 B T.

A fir, 20 ins. diam., bears S.41°E., 108 lks. dist., mkd. T 30 S R 1 E S 24 B T.

A fir, 15 ins. diam., bears S.47°W., 34 lks. dist., mkd. T 30 S R 1 E S 23 B T.

A fir, 8 ins. diam., bears N.33°W., 68 lks. dist., mkd. T 30 S R 1 E S 14 B T.

Land, mountainous.

Soil, sandy loam and rocky; 3rd and 4th rate.

Timber, fir hemlock, cedar, pine, and yew.

Undergrowth, vinemaple, 2nd growth, serviceberry, huckle berry, rhofofendron, spirea, and salal.

N.89° 53' W., on a random line bet. secs. 14 and 23.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.08 Intersect N. and S. line, 2 lks. S. of the cor. of secs. 14, 15, 22, and 23.

Thence

S.89° 52' E., on true line bet. secs. 14 and 23.

Asc. 28 ft. along N. slope, through heavy timber and dense undergrowth.

3.00 Spur, slopes N.; desc. 133 ft. over NE. slope

4.26 Bald Ridges Trial, bears N.25°W. and S.

8.45 Draw, drains N.25°E.; asc 65 ft. over NW. Slope.

12.60 Point of spur, slopes N.; desc. 8 ft. over NE. slope.

13.82 Head of small ravine, course NW.; asc 33 ft. over NW. slope.

16.00 Spur, slopes N.; desc. 270 ft. over NE. slope.

27.15 Ravine, course N.; asc. 60 ft. over NW. slope.

30.00 Point of spur, slopes N.; desc. 170 ft. over NE. slope.

37.00 Enter creek bottom, bears NW. and SE.

40.04 Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground to bedrock, and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   $\frac{S\ 14}{S\ 23}$   
1937

from which

A fir, 30 ins. diam., bears N.25°W., 88 lks. dist., mkd.  $\frac{1}{4}$  S 14 B T.

A fir, 20 ins. diam., bears S.18°E., 70 lks. dist., mkd.  $\frac{1}{4}$  S 23 B T.

Continue along creek bottom.