

Subdivision of Part of T. 30 S., R. 1 E.

CHAINS

- 43.00 Squaw Creek, 50 lks. wide, course N.30°W.; asc. 325 ft. over SW. slope.
- 55.20 Spur, slopes SW.; desc. 100 ft. over SE. slope.
- 59.45 Spring branch, 1 lk. wide, course S.60°W.; sac. 630 ft. over NW. slope.
- 76.00 Spur, slopes SW.; asc. 85 ft. over SW. slope.
- 80.08 The cor. fo secs. 13, 14, 23, and 24.

Land, mountainous.
 Soil, sandy loam and rocky; 3rd and 4th rate.
 Timber, fir, pine, hemlock, cedar, oak, and yew.
 Undergrowth, rhododendron, chinquapin, vinemaple, Oregon grape, huckleberry, and salal.

N.89°E., on a random line bet. secs. 13 and 24.

- 40.00 Set temp. $\frac{1}{4}$ sec. cor.
- 78.37 Intersect E bdy. of Tp. at the cor. of secs. 13 and 24 only, previously described.
- Thence
- S89° 52' W., on true line bet. secs. 13 and 24.
- Desc. 35 ft. over rolling N. slope, through heavy timber and dense undergrowth.
- 21.50 Ridge, bears NW. and SE.; desc. 245 ft. over W. slope, changing to SW. slope.
- 27.95 North and South Trail, bears N. and S.30°E.
- 34.30 Draw, drains N.70°W.; desc. 90 ft. over NW. slope.
- 38.37 Set an iron post, 3 ft. long, 1 in. diam., 15 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S 13
 $\frac{1}{4}$ S 24
 1937

from which

A fir, 12 ins. diam., bears N.63°E., 20 lks. dist., mkd. $\frac{1}{4}$ S 13 B T.

A fir, 15 ins. diam., bears S.25°E., 30 lks. dist., mkd. $\frac{1}{4}$ S 24 B T.

Desc. 150 ft. over W. slope.

- 42.30 Same draw, drains S.60°W.; desc. 15 ft. over SW. slope.
- 43.90 Draw, drains SW.; asc. 55 ft. over SE. slope.
- 53.70 Spur, slopes S.30°W.; desc. 525 ft. over SW. slope.
- 78.37 The cor. of secs. 13, 14, 23, and 24.

Land, mountainous.
 Soil, sandy loam and rocky; 3rd and 4th rate.
 Timber, fir, pine, cedar, and madrona.
 Undergrowth, 2nd growth, vinemaple, spirea, dogwood, hazel, huckleberry, and salal.