

County Surveyor's Record, Douglas County, Oregon

Subdivision of Part of T. 30 S., R. 1 E.

CHAINS	
	N.0° 01' W., bet secs. 13 and 14.
	Asc. 23 ft. over SW. slope, through heavy timber and dense undergrowth.
2.20	Spur, slopes SW. from N.70°E.; desc. 130 ft. over NW. slope.
10.30	Draw, drains W.; asc. 13 ft. over SW. slope.
12.20	Point of spur, slopes W.; desc. 65 ft. over NW. slope.
14.45	Spring branch, 1 lk. wide, corse S.50°W.; asc 425 ft. over S. slope, changing to SW. slope.
28.96	North and South Trail, bears NW. and E.
34.25	Ridge, bears N.70°W. and S.70°E.; desc. 70 ft. over NW. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \\ S14 S13 \\ \\ 1937 \end{array}$
	from which
	A cedar, 47 ins. diam., bears S.49°E., 34 lks. dist., mkd. $\frac{1}{4}$ S 13 B T.
	A fir, 40 ins. diam., bears S. 66°W., 52 lks. dist., mkd. $\frac{1}{4}$ S 14 B T.
	Desc. 860 ft. over NW. slope, changing to N. slope.
69.28	Creek, 6 lks. wide, corse W.; asc. 350 ft. over SW. slope, changing to SE. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 11, 12, 13, and 14, with brass cap vkd.
	$\begin{array}{c} T30S R1E \\ \hline S11 S12 \\ \hline S14 S13 \\ 1937 \end{array}$
	from which
	A fir, 15 ins. diam., bears N.67°E., 53 lks. dist., mkd. T 30 S R 1 E S 12 B T.
	A fir, 37 ins. diam., bears S.42°E., 42 lks. dist., mkd. T 30 S R 1 E S 13 B T.
	A fir, 15 ins. diam., bears S. 36°W., 59 lks. dist., mkd. T 30 S R 1 E S 14 B. T.
	A fir, 8 ins. diam., bears N.26°W., 40 lks. dist., mkd. T 30 S R 1 E S 11 B T.
	Land, mountainous. Soil, sandy loam and rocky; 3rd and 4th rate. Timber, fir, cedar, hemlock, pine, and yew. Undergrowth, vinemaple, huckleberry, 2nd growth, and salal.