

County Surveyor's Record, Douglas County, Oregon

Subdivision of Part of T. 30 S., R.1 E.

CHAINS	
30.85	Draw, drains SW.; asc. 16 ft. over SE. slope.
35.40	Spur, slopes SW.; desc. 85 ft. over W. slope.
38.40	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{l} S 12 \\ S 13 \end{array}$
	1937
	from which
	A fir, 23 ins. diam., bears N.55°E., 88 lks. dist., mkd. $\frac{1}{4}$ S 12 B T.
	A white fir, 18 ins. diam., bears S.13°E., 27 lks. dist., mkd. $\frac{1}{4}$ S 13 B T.
	Desc. 140 ft. over NW. slope.
42.33	Creek, 2 lks. wide, course SW.; asc 100 ft. over broken SE. slope.
44.65	Dry wash, 2 lks. wide, course S30°W/
55.60	Spur, slopes SW.; desc. 170 ft. over NW. slope.
59.40	Dry wash, 8 lks. wide, course SW.; asc. 185 ft. over SE. slope.
73.00	Spur, slopes SW.; desc. 85 ft. over W. slope.
75.60	Draw, drains S.30°W.; asc. 45 ft. over SE. slope.
78.40	The cor. of secs. 11, 12, 13, and 14.
	Land, mountainous. Soil, sandy loam and rocky; 2nd and 4th rate. Timber, fir, hemlock, pine, cedar, maple, and yew. Undergrowth, vinemaple, huckleberry, spirea, chinquapin, and salal.
	N.0° 01' W., bet. secs. 11 and 12.
	Asc. 80 ft. over SE. slope, through heavy timber and dense undergrowth.
3.00	Spur, slopes SW.; desc. 47 ft. over NW. slope.
5.02	Draw, drains S.85°W.; asc. 520 ft. over SW. slope.
21.75	Spur, slopes N.70°W.; desc. 695 ft. over NE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{l} S 11 \\ S 12 \end{array}$
	1937
	from which
	A fir, 50 ins. diam., bears N.51°E., 34 lks. dist., mkd. $\frac{1}{4}$ S 12 B T.
	A fir, 50 ins. diam., bears S.81°W., 73 lks. dist., mkd. $\frac{1}{4}$ S 11 B T.