

County Surveyor's Record, Douglas County, Oregon

Subdivision of Part of T. 30 S., R. 1 E.

CHAINS

Desc. 70 ft. over NE. slope.

41.95 Creek, 1 lk. wide , course N. .; asc. 25 ft. over SW.

45.80 Spur, slopes W. desc. 40 ft. over NW. slope.

47.40 Draw, drains * W.: asc. 115 ft. over SW. slope.

63.00 Spur, slopes * N.80°W.; desc. 45 ft. over NW. slope.

71.40 Spur, slopes * NW.; desc. 250 ft. over NE. slope.

80.00 Set an iron post 3 ft. long, 1 in. diam., 27 ins. in the ground, for cor. of secs. 1, 2, 11, and 12, with brass cap mkd.

T30S R1E
S 2 | S 1
S11 | S12
1937

from which

A fir, 22 ins. diam., bears N.75°E., 39lks. dist., mkd. T 30 S R 1 E S 1 B T.

A white fir, 12 ins. diam., bears S.43°E., 43 lks. dist., mkd. T 30 S R 1 E S 12 B T.

A fir, 12 ins. diam., bears S.44°W., 82 lks. dist., mkd. T 30 S R 1 E S 11 B T.

A yew, 6 ins. diam., bears N.69°W., 43 lks. dist., mkd. T 30 S R 1 E S 2 B T.

Land, mountainous.
Soil, sandy loam and rocky; 2nd and 4th rate.
Timber, fir, cedar, yew, hemlock, and madrona.
Undergrowth, vinemaple, 2nd growth, rhododendron, spirea, mamzanita, huckleberry, and salal.

West, on a random line get. secs. 2 and 11.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.98 Intersect N. and S. line, 16 lks. N. of cor. of secs. 2, 3, 10, and 11.

Thence

N.89° 53' E., on true line bet. secs. 2 and 11.

Asc. 87 ft. over NW. slope, through heavy timber and dense undergrowth.

5.80 Point of spur, slopes N.; desc. 60 ft. over NE. slope.

9.22 Draw, drains N.30°W.; asc. 275 ft. over NW. slope.

19.10 Spur, slopes N.; desc. 120 ft. over NE. slope.

29.20 Head of draw, drains N.; asc. 175 ft. over NE. slope.

39.99 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S 2
S 11

1937

* - When originally typed the Xerox copies could not be read per LL (Lorraine Lewis) Information added 2/10/2010 from the orig. GLO/BLM notes on the internet. -- JC - DCSO notes on the internet