

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the W. Bdy., T. 22 S., R. 8 W.

CHAINS

1960 dependent resurvey.

N. 0° 28' E., along W. bdy. of sec. 30, marking and blazing the true line.

Ascend 102 ft. over SW. slope through heavy timber and dense undergrowth.

6.20

The closing cor. of secs. 25 and 36, T. 22 S., R. 9 W., perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1963, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

		T 22 S	
R	S 25	CC	R
9			8
W	S 36		W
		1963	

*Fd OK. by  
R. Luckman  
1-13-83  
M 93-41*

from which the original bearing trees

A fir, 54 ins. diam., bears S. 88° E., 68 lks. dist., with fragmentary scribe marks visible on opened blaze. (Record, S. 86° E.)

A fir, 29 ins. diam., bears S. 25° W., 82 lks. dist., with a healed blaze. This tree re-marked by Godfrey in 1963, blaze nearly healed.

A fir snag, 50 ins. diam., bears N. 67° W., 64 lks. dist., with a healed blaze. (Record, 66 lks.)

and trees marked by Godfrey

A fir, 19 ins. diam., bears N. 66° E., 33 lks. dist., with fragmentary scribe marks visible on nearly healed blaze.

A fir, 9 ins. diam., bears N. 39° W., 25 lks. dist., with a healed blaze.

Ascend 138 ft. over SW. slope.

9.00

Spur ridge, bears NW. and SE.; desc. 671 ft. over broken NE. slope.

38.35

Graveled road, 30 lks. wide, bears N. 60° W. and S 60° E., curving to NE.

40.00

Record distance for the 1/4 sec. cor. of sec. 30 only; there is no remaining evidence of the original corner.

45.20

Point for the 1/4 sec. cor. of sec. 25 only, T. 22 S., R. 9 W.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

		1/4
T 22 S		
R 9 W		
S 24		
		1965

from which