

Dependent Resurvey, Portion of Subdivisional Lines, T. 22 S., R. 8 W.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} \text{S } 11 \\ \text{S } 14 \end{array}$$

T 22 S R 8 W
1967

from which

A fir, 5 ins. diam., bears N. 82° W., 18 lks. dist., mkd. $\frac{1}{4}$ S11 BT.

A fir, 5 ins. diam., bears S. 39° E., 7 lks. dist., mkd. $\frac{1}{4}$ S 14 BT.

Descend 300 ft. over NW. slope.

48.40 Creek, 3 lks. wide, course N. 35° E.; asc. 350 ft. over SE. slope.

61.00 Spur, slopes SE.; desc. 2 ft. over SW. slope.

61.74 Point for the W $1/16$ sec. cor. of secs. 11 and 14.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\text{W } 1/16 \begin{array}{l} \text{S } 11 \\ \text{S } 14 \end{array}$$

1967

from which

A fir, 38 ins. diam., bears N. 35° E., 195 lks. dist., mkd. W $1/16$ S11 BT.

A fir, 8 ins. diam., bears N. 44° W., 86 lks. dist., mkd. W $1/16$ S11 BT.

No suitable tree available in section 14.

Descend 40 ft. over SE. slope.

65.00 Ravine, drains S. 40° E.; asc. 100 ft. over E. slope, changing to SE. slope.

77.70 Top of ascent, slopes S.; desc. 5 ft. over SE. slope.

82.32 The cor. of secs. 10, 11, 14, and 15, perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1962, monumented with an iron post, $1\frac{1}{2}$ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 22 S
 $\begin{array}{l} \text{S } 10 \text{ | } \text{S } 11 \\ \text{S } 15 \text{ | } \text{S } 14 \end{array}$
R 8 W
1962

from which the original bearing trees

A down and decayed white oak, size indeterminate, bears S. $10\frac{1}{2}^\circ$ E., 336 lks. dist., with no marks remaining.