

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 22 S., R. 8 W.

## CHAINS

A fir, 40 ins. diam., bears S.  $48\frac{1}{2}^{\circ}$  W., 315 lks. dist., with healed blaze and scribe marks  
T22S R8W visible on bark blaze.

and trees marked by Godfrey

A fir, 20 ins. diam., bears N.  $2^{\circ}$  E., 36 lks. dist., with healed double blaze.

A fir, 18 ins. diam., bears S.  $18^{\circ}$  E., 69 lks. dist., with healed double blaze.

A fir, 16 ins. diam., bears N.  $40^{\circ}$  W., 16 lks. dist., with healed double blaze.

and a new bearing tree

A fir, 13 ins. diam., bears S.  $72^{\circ}$  W., 117 lks. dist., mkd. T22S R8W S15 BT.

Land, mountainous.

Soil, sandy clay loam.

Timber, scattering fir, hemlock, cedar, maple, and alder; undergrowth, vine maple, hazel, huckleberry, arrowwood, salmonberry, thimbleberry, poison oak, salal, and fern.

N.  $0^{\circ} 30'$  E., bet. secs. 10 and 11.

Ascend 235 ft. over SW. slope, through scattering timber and dense undergrowth.

7.10 Dirt road, 15 lks. wide, bears E. and W.

19.95 From this point, a local corner bears West, 0.10 chs. dist., monumented with an iron pipe,  $1\frac{1}{2}$  ins. diam., firmly set, projecting 36 ins. above ground.

20.30 Ridge, bears N.  $80^{\circ}$  E. and S.  $80^{\circ}$  W.; desc. 650 ft. over NW. slope.

39.30 Little Paradise Creek, 20 lks. wide, course W.; asc. 8 ft. over S. slope  
The  $\frac{1}{4}$  sec. cor. of secs. 10 and 11, perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1962, monumented with a sandstone,  $24 \times 4 \times 4$  ins., firmly set, projecting 12 ins. above ground, marked X on top,  $\frac{1}{4}$  on N.; S11 on E., and S10 on W. face, from which an original bearing tree

A sawed fir stump, 40 ins. diam., bears S.  $54^{\circ}$  E., 177 lks. dist., with old axe marks visible on burned and rotted blaze.

and bearing trees marked by Godfrey

A fir, 23 ins. diam., bears S.  $7^{\circ}$  E., 88 lks. dist., with healed double blaze.

A fir, 20 ins. diam., bears S.  $18^{\circ}$  W., 110 lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the groynd, with brass cap mkd.