

County Surveyor's Record, Douglas County, Oregon

Dependent Rewurvey, Portion of Subdivisional Lines, T. 22 S., R. 8 W.

CHAINS
20.04

Point for the E 1/16 sec. cor. of secs. 19 and 30.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{E } 1/16 \text{ } \frac{\text{S } 19}{\text{S } 30} \\ 1965 \end{array}$$

from which

A fir, 10 ins. diam., bears N. 25°W., 49½ lks. dist., mkd. E 1/16 S19 BT.

A fir, 22 ins. diam., bears S. 57°W., 23 lks. dist., mkd. E 1/16 S30 BT.

Descend 65 ft. over SW. slope.

24.65 Creek, 3 lks. wide, course N. 50° W.; asc. 186 ft. over NE. slope.

32.00 Spur ridge, slopes N. 15° E. and S. 15° E.; desc. 86 ft. along N. slope.

40.08 Point for the ¼ sec. cor. of secs. 19 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \text{ } \frac{\text{S } 19}{\text{S } 30} \\ \text{T } 22 \text{ S } \text{ R } 8 \text{ W} \\ 1965 \end{array}$$

from which

A fir, 19 ins. diam., bears N. 18° W., 37½ lks. dist., mkd. ¼ S19 BT.

A fir, 12 ins. diam., bears S. 29½° W., 32½ lks. dist., mkd. ¼ S30 BT.

Descend 267 ft. along a N. slope, changing to a broken NW. slope.

85.37 The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp.

Land, mountainous.
Soil, sandy clay loam.
Timber, fir, hemlock, cedar, alder, maple, chinquapin, myrtle, and madrone; undergrowth, vinemaple, salal, hazel, arrowwood, huckleberry, blackberry, salmonberry, poison oak, ceanothus, manzanita, rhododendron, and fern.

From the corner of secs. 19, 20, 29, and 30.

N. 4° 01' W., bet. secs. 19 and 20.

Ascend 89 ft. over S. slope changing to SW. slope, a ross old logged area through dense brush.

12.95 Spur, slopes S. 80°W., desc. 130 ft. over broken N. slope.