

Dependent Resurvey, Portion of Subdivisional Lines, T. 22 S., R. 8 W.

## CHAINS

- 19.10 Dirt road, 15 lks. wide, bears N. 70° E. and S. 70° W.
- 20.87 Point for the S 1/16 sec. cor. of secs. 19 and 20.  
Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
- S 1/16  
S 19 | S 20  
1965
- from which
- A fir, 6 ins. diam., bears S. 45° E., 36 lks. dist., mkd. S 1/16 S20 BT.
- A fir, 4 ins. diam., bears S. 67½° W., 95 lks. dist., mkd. S 1/16 S19 BT.
- Descend 89 ft. over N. slope.
- 23.25 Creek, 2 lks. wide, course W.; asc. 135 ft. over SW. slope.
- 30.35 Spur, slopes W.; desc. 91 ft. over NW. slope.
- 34.70 Ravine, drains W.; asc. 27 ft. over SW. slope.
- 41.74 The ¼ sec. cor. of secs. 19 and 20, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.
- ¼  
S 19 | S 20  
T 22 S R 8 W  
1960
- from which an original bearing tree
- A broken white fir snag, 22 ins. diam., bears N. 45° E., 20 lks. dist., with scribe mark S visible on opened blaze.
- and bearing trees marked by Floyd A. Brooks, in 1960
- A white fir, 12 ins. diam., bears S. 16° E., 96 lks. dist., with a healed blaze.
- A douglas fir snag, 20 ins. diam., bears N. 46½° W., 24 lks. dist., with fragmentary scribe marks visible on partly healed blaze.
- and a bearing tree marked by the County Surveyor in 1963
- A white fir, 17 ins. diam., bears S. 60° W., 37½ lks. dist., with scribe marks ¼ S19 CS BT. visible on partly healed double blaze.
- 
- N. 2° 35' W., beginning new measurement.
- Ascend 57 ft. over SW. slope.
- 3.95 Spur, slopes W.; desc. 63 ft. over NW. slope.
- 12.80 Bottom of descent, slopes W.; asc. 59 ft. over SW. slope.