

Dependent Resurvey, Portion of Subdivisiona. Lines, T. 22 S., R. 8 W.

CHAINS

S. 87° 50' W., bet. secs. 18 and 19.

Descend 317 ft. over general W. slope, across logged area.

32.90 Creek, 1 lk. wide, course S. 40° W.; asc. 86 ft. over SE. slope, changing to S. slope.

40.02 The $\frac{1}{4}$ sec. cor. of secs. 18 and 19, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.
$$\frac{1}{4} \begin{array}{l} S 18 \\ S 19 \end{array}$$
 1931

from which the trees marked by George F. Rigby

A fir, 53 ins. diam., bears N. 36° W., 26 lks. dist., with fragmentary scribe marks visible on nearly healed blaze.

A down fir, 36 ins. diam., bears S. 3 $\frac{1}{2}$ ° W., 59 lks. dist., with a healed blaze.

and trees marked by the County Surveyor in 1963

A fir, 21 ins. diam., bears N. 52°W., 17 lks. dist., with scribe marks $\frac{1}{4}$ S18 CS BT. visible on unhealed blaze.A hemlock, 7 ins. diam., bears S. 28 $\frac{1}{4}$ °E., 54 $\frac{1}{2}$ lks. dist., with scribe marks $\frac{1}{4}$ S19 CS BT visible on unhealed blaze.

S. 87° 58' W., beginning new measurement.

Ascend 29 ft. along S. slope, through dense young timber and brush.

2.10 Top of ascent, slopes S.; desc. 19 ft. along S. slope.

8.65 Spur, slopes SW.; desc. 177 ft. over NW. slope.

20.13 The W 1/16 sec. cor. of secs. 18 and 19, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

$$W \frac{1}{16} \begin{array}{l} S 18 \\ S 19 \end{array}$$
 1931

from which the trees marked by George F. rigby

A down hemlock, 19 ins. diam., bears N. 59°W., 32 lks. dist., with a healed blaze.

A down hemlock, 22 ins. diam., bears S. 41° W., 36 lks. dist., with a healed blaze.

and new bearing trees

A white fir, 13 ins. diam., bears N. 6° E., 96 lks. dist., mkd. W 1/16 S18 BT.

A hemlock, 14 ins. diam., bears S. 57°E., 46 lks. dist., mkd. W 1/16 S19 BT.