

County Surveyor's Record, Douglas County, Oregon

Resurvey, Portion of Boundaries, Claim No. 45, T. 22 S., R. 8 W.

CHAINS

from which

A hemlock, 8 ins. diam., bears N. $78\frac{1}{2}^{\circ}$ E.,
115 lks. dist., mkd. T22S R8W C45 BT.

A hemlock, 13 ins. diam., bears N. 50° W.,
51 lks. dist., mkd. T22S R8W S29 BT.

N. $0^{\circ} 30'$ W., along the W. bdy. of Claim No. 45.

Descend 35 ft. over NE. slope, through moderate timber
and undergrowth.

1.20 Creek, 2 lks. wide, course S. 85° E.; asc. 188 ft. over
SE. slope.

11.75 Spur, slopes S. 50° E.; desc. 102 ft. over NE. slope.

18.37 Point for the closing cor. at intersection with the
E. and W. center line of sec. 29, hereinafter described.

Ascend 5 ft. along broken E. slope.

56.79 The closing cor. of secs. 20 and 29, heretofore
described.

Ascend 28 ft. over SE. slope.

58.89 The NW. cor. of Claim No. 45, monumented with a maple
tree, 23 ins. diam., with scribe mark 8 visible on
opened blaze, from which the remaining original bearing
tree:

A white fir snag, 41 ins. diam., bears
S. 4° E., 38 lks. dist., with decayed blaze,
no marks visible. (Record, S. 40° E.)

add new bearing trees and a reference monument

A fir, 5 ins. diam., bears N. 15° E., 54 lks.
dist., mkd. T22S R8W S20 BT.

A white fir, 6 ins. diam., bears S. 7° E.,
34 lks. dist., mkd. T22S R8W C45 BT.

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set
22 ins. in the ground for a reference monument,
bears S. 76° W., 14 lks. dist., with brass cap
marked T22S R8W S20 RM 1965 and an arrow
pointing to the corner.

Subdivision of Section 19, T. 22 S., R. 8 W.

From the $\frac{1}{4}$ sec. cor. of secs. 19 and 30.

N. $5^{\circ} 35'$ W., along the N. and S. center line of sec.
19, marking and blazing the true line.

Descend 194 ft. over a N. slope, changing to a NE.
slope, through heavy timber and dense undergrowth.

9.85 Dirt road, 15 lks. wide, bears N. 60° W. and S. 60° E.

20.40 Bottom of descent, slopes E.; asc. 10 ft. over SE. slope.

22.075 Point for the center S $1/16$ sec. cor. of sec. 19.