

Subdivision of Section 19, T. 22 S., R. 8 W.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} C \\ S\ 1/16\ S\ 19 \\ C \\ 1965 \end{array}$$

from which

A fir, 15 ins. diam., bears N. $17\frac{1}{2}^\circ$ E., 79 lks. dist., mkd. CS $1/16$ S19 BT.

A fir, 17 ins. diam., bears S. 20° W., 95 lks. dist., mkd. CS $1/16$ S19 BT.

Ascend 25 ft. over SE. slope.

35.50 Spur, slopes S. 50° E.; desc. 230 ft. over NE. slope.

31.10 Creek, 3 lks. wide, course N. 65° W.; asc. 200 ft. over SW. slope.

41.00 Spur, slopes N. 60° W.; desc. 75 ft. over NE. slope.

44.15 Point for the center $\frac{1}{4}$ sec. cor. of sec. 19, determined at the intersection of lines parallel to the N. half mile of the W. bdy. of sec. 19, and at a mean bearing of the W. half of the N. bdy. of sec. 19.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} C\ \frac{1}{4}\ S\ 19 \\ 1965 \end{array}$$

from which

A hemlock, 10 ins. diam., bears N. $16\frac{1}{2}^\circ$ E., $18\frac{1}{2}$ lks. dist., mkd. C $\frac{1}{4}$ S19 BT.

A hemlock, 6 ins. diam., bears N. 89° W., 39 lks. dist., mkd. C $\frac{1}{4}$ S19 BT.

N. $0^\circ 56'$ W., parallel to the W. bdy. of sec. 19; beginning new measurement.

Descend 50 ft. over NE. slope.

1.20 Ravine, drains N. 55° W.; asc. 30 ft. over SE. slope.

2.10 Spur, slopes W.; desc. 30 ft. over N. slope.

2.60 Creek, 2 lks. wide, course S. 70° W.; asc. 250 ft. over a general S. slope.

20.80 Spur, slopes W.; desc. 200 ft. over N. slope.

34.80 Creek, 2 lks. wide, course S. 60° W.; asc. 125 ft. over general S. slope.

39.63 The $\frac{1}{4}$ sec. cor. of secs. 18 and 19.

From the $\frac{1}{4}$ sec. cor. of secs. 19 and 20.

N. $83^\circ 19'$ W., along the E. and W. center line of sec. 19.