

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 19, T. 22 S., R. 8 W.

CHAINS

Ascend 25 ft. over broken SE. slope, through scattering timber and dense undergrowth.

8.60 Spur, slopes S. 30° W. ; desc. 120 ft. over NW. slope.

20.79 Point for the center E 1/16 sec. cor. of sec. 19.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

C $\frac{E\ 1/16}{S\ 19}$ C
1965

from which

A fir, 15 ins. diam., bears N. 27° W., 62 lks. dist., mkd. CE 1/16 S19 BT.

A hemlock, 10 ins. diam., bears S. 5° W., 35½ lks. dist., mkd. CE 1/16 S19 BT.

Descend 100 ft. over NW. slope, shanging to a broken W. slope.

36.40 Ravine, drains N. 55° W.; asc. 40 ft. over NE. slope.

41.58 The center ¼ sec. cor. of sec. 19.

S. 88° 12' W., beginning new measurement.

Ascend 20 ft. over NE. slope.

3.60 Spur, slopes N. 65° W.; desc. 230 ft. over SW. slope.

10.40 Creek, 1 lk. wide, course N. 30° W.; asc. 480 ft. over NE. slope.

30.10 Dirt road, 15 lks. wide, brars N. 15° E. and S. 15° W.

33.20 Spur, slopes S. 10° E.; desc. 45 ft. over SW. slope.

38.30 Ravine, drains S.; asc. 25 ft. over SE. slope.

40.20 Dirt road, 15 lks. wide, bears N. 30° W. and S. 30° E.

40.15 The ¼ sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp.

From the E 1/16 sec. cor. of secs. 19 and 30.

N. 4° 49' W., along the N. and S. center line of the SE¼ of sec. 19.

Ascend 150 ft. over SW. slope, through heavy timber and desce undergrowth.

9.50 Spur, slopes S. 60° W.; desc. 90 ft. over NW. slope.

21.42 Point for the SE 1/16 sec. cor. of sec. 19, at inter-section with the E. and W. center line of the SE¼.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

SE 1/16 S 19
1965