

14129 County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 19, T. 22 S., R. 8 W.

CHAINS

from which

A fir, 11 ins. diam., bears S. 85° E., 95 lks. dist., mkd. SE 1/16 S19 BT.

A fir, 7 ins. diam., bears S. 17° W., 12 lks. dist., mkd. SE 1/16 S19 BT.

Corner falls on a spur, slopes N. 35° W.; desc. 130 ft. over NE. slope.

25.80 Creek, 3 lks. wide, course S. 80° W.; asc. 153 ft. over S. slope.

36.35 Spur, slopes W.; desc. 17 ft. over NW. slope.

42.93 The center E 1/16 sec. cor. of sec. 19.

From the S 1/16 sec. cor. of secs. 19 and 20.

N. 84° 52' W., along the E. and W. center line of the SE 1/4 of sec. 19.

Ascend 45 ft. over NE. slope, through scattering timber and dense undergrowth.

6.60 Spur, slopes N. 55° W.; desc. 220 ft. over SW. slope.

Creek, 1 lk. wide, course N. 40° E.; asc. 40 ft. over NE slope.

20.42 The SE 1/16 sec. cor. of sec. 19.

Corner falls on a spur, slopes N. 35° W.; desc. 70 ft. over W. slope.

24.69 Ravine, frains NW.; asc. 25 ft. over NE. slope.

28.00 Spur, slopes N. 30° W.; desc. 170 ft. over W. slope.

32.45 Creek, 2 lks. wide, course N. 20° W.; asc. 140 ft. over NE. slope.

40.82 The center S 1/16 sec. cor. of sec. 19.

Subdivision of Section 29, T. 22 S., R. 8 W.

From the 1/4 sec. cor. of secs. 29 and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap, marked and witnessed as described in the official record of the 1960 dependent resurvey.

N. 1° 57' W., along the N. and S. center line of sec. 29.

Ascend 92 ft. over SE. slope, through scattering timber and dense undergrowth.

6.30 Spur, slopes E.; desc. 126 ft. over broken NE. slope.

17.00 Creek, 3 lks. wide, course S. 80° E.; asc. 42 ft. over broken SE. slope.

18.85 Abandoned dirt road, 15 lks. wide, bears N. 80° W. and S. 80° E.