

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 29, T. 22 S., R. 8 W.

CHAINS
19.83

Point for the center S 1/16 sec. cor. of sec. 29.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} C \\ S\ 1/16\ |S\ 29 \\ C \\ 1965 \end{array}$$

from which

A fir, 5 ins. diam., bears S. 29° W., 10½ lks. dist., mkd. CS 1/16 S29 BT.

A fir, 10 ins. diam., bears N. 34° W., 66 lks. dist., mkd. CS 1/16 S29 BT.

No suitable tree available E. of line.

Thence over level land.

21.10

Point for the closing cor. at intersection with the S. bdy. of Claim No. 45.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} C\ 45 \\ C \\ \hline C\ C\ |S\ 29 \\ C \\ T\ 22\ S\ R\ 8\ W \\ 1965 \end{array}$$

from which

A fir, 6 ins. diam., bears S. 56° E., 111½ lks. dist., mkd. T22S R8W S29 CC BT.

A fir, 9 ins. diam., bears S. 26° W., 73 lks. dist., mkd. T22S R8W S29 CC BT.

From this point the SW. cor. of Claim No. 45, bears S. 89° 33' W., 16.06 chs. dist.

Ascend 22 ft. along gentle E. slope.

25.20

Sawyer Creek Road, 20 lks. wide, bears N. 64° E. and S. 64° W.

39.66

Point for the center ¼ sec. cor. of sec. 29, at intersection with the E. and W. center line.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} C\ \frac{1}{4}\ S\ 29 \\ 1964 \end{array}$$

from which

A fir, 6 ins. diam., bears S. 6½° E., 302 lks. dist., mkd. C¼ S29 BT.

A white fir, 19 ins. diam., bears S. 86° W., 336 lks. dist., mkd. C¼ S29 BT.

Descend 127 ft. over gentle NE. slope.

77.77

The ¼ sec cor. of secs. 20 and 29.