

Subdivision of Section 29, T. 22 S., R. 8 W.

CHAINS

From the $\frac{1}{4}$ sec. cor. of secs. 29 and 30.N. $88^{\circ} 48'$ E., along the E. and W. center line of sec. 29.

Descend 478 ft. over general E. slope, through heavy timber and dense undergrowth.

18.85

Point for the center W $\frac{1}{16}$ sec. cor. of sec. 29.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

W $\frac{1}{16}$
 C ————— C
 S 29
 1965

from which

A fir, 8 ins. diam., bears N. 16° W., 52 lks. dist., mkd. CW $\frac{1}{16}$ S29 BT.A white fir, 13 ins. diam., bears S. 86° W., 40 lks. dist., mkd. CW $\frac{1}{16}$ S29 BT.

Descend 65 ft. over SE. slope.

22.11

Point for closing cor. at the intersection with the W. bdy. of Claim No. 45.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.

T 22 S R 8 W
 C $\frac{C C}{S 29}$ C C 45
 1965

from which

A maple, 41 ins. diam., bears N. $54\frac{1}{4}^{\circ}$ W., 100 lks. dist., mkd. T22S R8W S29 CC BT.An ash, 5 ins. diam., bears S. $68\frac{1}{2}^{\circ}$ W., $7\frac{1}{2}$ lks. dist., mkd. T22S R8W S29 CC BT.From this point the SW. cor. of Claim No. 45, bears S. $0^{\circ} 30'$ E., 18.37 chs. dist.

Descend 145 ft. over general E. slope.

37.70

The center $\frac{1}{4}$ sec. cor. of sec. 29.

Descend 150 ft. over general E. slope, across open field.

67.65

Sawyer Creek Road, 25 lks. wide, bears N. 35° E. and S. 35° W.

69.25

Sawyer Creek, 10 lks. wide, course N. 40° E.; asc. 10 ft. over NW. slope.

72.46

The $\frac{1}{4}$ sec. cor. of secs. 28 and 29.From the W $\frac{1}{16}$ sec. cor. of sec. 29 and 32, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting