

County Surveyor's Record, Douglas County, Oregon

Remonumentation of Certain Original Corner Points,
T. 33 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 S	T 33 S
R 8 W	S 6
S 1	S 7
	R 7 W
	1966

from which new bearing trees

A chinquapin, 6 ins. diam., bears N. 25° E., 90 lks. dist., mkd. T33S R7W S6 BT.

A fir, 26 ins. diam., bears S. 38° E., 70 lks. dist., mkd. T33S R7W S7 BT.

Subdivisions, T. 33 S., R. 7 W.,
Willamette Meridian, Oregon

(Remonumenting a corner established by Oscar F. Thiel, in 1901)

The ¼ sec. cor. of secs. 7 and 8, monumented with the broken original granite stone, 22 x 8 x 6 ins., firmly set, 10 ins. in the ground, marked ¼ on W. face, from which the remaining original bearing tree:

A fir, 56 ins. diam., bears S. 1° W., 476 lks. dist., mkd. ¼ S7 BT on a bark blaze. (Record, 474 lks.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 S	R 7 W
S 7	S 8
	¼
	1966

from which new bearing trees

A live oak, 6 ins. diam., bears S. 27° E., 25 lks. dist., mkd. ¼ S8 BT.

A fir, 18 ins. diam., bears N. 16° W., 136 lks. dist., mkd. ¼ S7 BT.

Deposit corner stone alongside iron post.