

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of E. Bdy., T. 20 S., R. 8 W.

CHAINS

from which bearing trees mkd., by Tillman in 1950

A sawed and burned fir stump, 45 ins. diam., bears S.  $85\frac{1}{2}^\circ$  W., 62 lks. dist., with burned out blaze, no scribe marks visible  
fir

A sawed and burned/stump, 44 ins. diam., bears N.  $75\frac{1}{2}^\circ$  W., 136 lks. dist., with scribe marks BT visible on remaining portion of opened blaze. (Record bearing, N.  $70\frac{1}{2}^\circ$  W.)


No live bearing trees available within limits in sec. 25.

Set a steel fence post alongside the iron post.

N.  $1^\circ 13'$  E., beginning new measurement.

Descend 130 ft. over steep rocky N. slope, through open logged and burned area.

- 2.15 Head of ravine, drains NW.; asc. 20 ft. over steep SW. slope.
- 4.85 Top of ascent, slopes W.; desc. 180 ft. over NW. slope.
- 11.15 Ravine, drains W.; asc. 45 ft. over SW. slope, changing to rocky W. slope.
- 18.60 Point for the  $\frac{1}{2}$  sec. cor. of sec. 30 only, on the W. bdy. of T. 20 S., R. 7 W., hereinafter described.  
  
Ascend 7 ft. along steep rocky W. slope.
- 18.85 Top of ascent, slopes W.; desc. 270 ft. over steep rocky NW. slope.
- 22.00 Leave logged area, edge bears E. and W.; enter burned timber.
- 29.50 Creek, 2 lks. wide, course N. from S.  $20^\circ$  W.; desc. 30 ft. along creek.
- 33.90 Leave creek, course N.  $20^\circ$  W.; asc. 25 ft. over SW. slope.
- 36.70 Top of ascent, slopes W.; desc. 30 ft. over NW. slope.
- 39.84 The cor. of secs. 24 and 25 only, monumented with an iron post, 2 ins. diam., protruding 10 ins. above the ground, firmly set, with brass cap marked



from which the remaining original bearing trees mkd. by Wright

A burned fir, 60 ins. diam., bears S.  $71^\circ$  W., 84 lks. dist., with burned out blaze, no scribe marks visible. (record distance, 81 lks.)

A burned fir snag, 25 ins. diam., bears N.  $47^\circ$  W., 71 lks. dist., no marks remaining.

and a bearing tree mkd. by Tillman in 1950

A burned fir, 67 ins., diam., bears N.  $55\frac{3}{4}^\circ$  W., 123 $\frac{1}{2}$  lks. dist., mkd. with a healed blaze. (record bearing and distance, N.  $55^\circ$  W., 126 lks.)

Set a steel fence post alongside the iron post.