

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 20 S., R. 7 W.

CHAINS	
18.00	Pearl Creek, 6 lks. wide, course Se.; asc. 480 ft. over SE. slope.
39.64	Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 20 S R 7 W $\frac{1}{4}$ S 16 $\frac{1}{4}$ S 21 1966 </div> from which A fir, 12 ins. diam., bears N. 54 $\frac{1}{2}$ ° E., 66 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S16 BT. A fir, 20 ins. diam., bears S. 3° E., 54 lks. dist., mkd. $\frac{1}{4}$ S21 BT. Set a steel fence post alongside the iron post. The cor. is located on top of ascent, slopes S. Descend 150 ft. along broken S. Slope.
51.60	Wet ravine, drains SE.; asc. 400 ft. over steep NE. slope.
58.00	Abandoned trail, bears N. 10° E. and S. 15° W.
59.00	Ridge, dividing Pearl Creek and Yellow Creek drainages, bears N. 10° W. and S. 10° E.; desc. 170 ft. over steep SW. slope.
59.70	Dirt road, 15 lks. wide, bears N. 10° W. and S. 10° E.
64.30	Ravine, drains S. 25° W.; asc. 35 ft. over SE. slope.
66.80	Spur, slopes S.; continue along broken S. slope.
72.25	Head of ravine, drains SE.; asc. 120 ft. over SE. slope.
75.05	Spur ridge, bears N. 25° E. and S.; desc 195 ft. over steep rocky NW slope.
79.28	The cor. sec. 16, 17, 20 and 21, perpetuated and recorded by the Douglas County Surveyor in September 1966, monumented with an iron post, 1 $\frac{1}{4}$ ins. diam., protruding 18 ins. above the ground, firmly set in a mound of stone, 3 ft. base, 1 ft. high, with 2 $\frac{1}{4}$ inch brass cap mkd. <div style="text-align: center;"> County Surveyors Office T 20 S $\frac{1}{4}$ S 17 $\frac{1}{4}$ S 16 $\frac{1}{4}$ S 20 $\frac{1}{4}$ S 21 R 7 W 1966 </div> from which the remaining original bearing tree A burned fir, 50 ins. diam., bears N. 10° E., 40 lks. dist., with scribe marks S16 visible on partially opened blaze. (Record bearing, N. 8° E.) and bearing trees mkd. by the County Surveyor in September 1966. A burned fir, 9 ins. diam., bears N. 9° E., 13 lks. dist., mkd. T20S R7W S16 CS BT on unhealed double blaze. A burned maple, 20 ins. diam., bears S. 30° E., 12 lks. dist., mkd. T20S R7W S21 CS BT on unhealed double blaze.