

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T 20 S., R. 7 W.

CHAINS

A burned fir, 9 ins. diam., bears S. $9\frac{1}{2}^{\circ}$ W., $32\frac{1}{2}$ lks. dist., mkd. T20S R7W S20 CS BT on unhealed double blaze.

A burned fir, 20 ins. diam., bears N. 25° W., 106 lks. dist., mkd. T20S R7W S17 CS BT on unhealed double blaze.

Set a steel fence post alongside the iron post.

From this point, United States Coast and Geodetic Survey triangulation station PEARL, 1953, bears N. $62^{\circ} 28'$ E., 21.92 chs. dist.

Land, mountainous.

Soil, rocky clay with sandstone outcroppings.

Timber, burned fir, hemlock, cedar, maple, alder, dogwood, and chinquapin; undergrowth, burned off except for patches of vine maple, salal, hazel, Oregon grape, and fern.

The cor. of secs. 29, 30, and 31, 32, perpetuated and recorded by the Douglas County Surveyor in September 1966, monumented with an iron post, $1\frac{1}{4}$ ins. diam., protruding 10 ins above the ground, firmly set, with $2\frac{1}{4}$ inch brass cap mkd.

County Surveyors Office

T 20 S	
S 30	S 29
S 31	S 32
R 7 W	
1966	

from which the original bearing trees

A cedar, 36 ins. diam., bears N. 3° E., 24 lks. dist., mkd. with a healed original blaze and rescribed T20S R7W S 29 CS BT on unhealed blaze.

A burned cedar, 72 ins. diam., bears S. 87° E., 39 lks. dist., mkd. with a healed blaze.

A burned cedar, 49 ins. diam., bears S. 8° W., 68 lks. dist., mkd. with a healed original blaze. and rescribed T20S R7W S31 CS BT on unhealed blaze.

A cedar, 49 ins. diam., bears N. $72\frac{1}{2}^{\circ}$ W., 120 lks. dist., mkd. with a healed blaze. (Record bearing, N. 74° W.)

and a bearing tree mkd. by the County Surveyor in September 1966.

A hemlock, 10 ins. diam., bears S. 21° E., 31 lks. dist., with scribe marks T20S R7W S32 CS BT visible on unhealed double blaze.

Set a steel fence post alongside the iron post.

The original sandstone, 18 x 14 x 8 ins., mkd. with 5 notches on E. and 1 notch on S. edge, has been reset alongside the iron post.

N. $89^{\circ} 53'$ W., bet. secs. 30 and 31.

Descend 3 ft. over NW. slope, through burned timber and undergrowth.

0.42 Dry bed of creek, 4 lks. wide, course NE.; asc. 140 ft. over E. slope, changing to NE. slope.

4.33 From this point a cor. of which I have no record, bears South, 0.095 chs. dist., monumented with a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, from which a bearing stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, from which a bearing tree:

A fir, 66 ins. diam., bears N. 18° E., 8 lks. dist., bark scribed BT S29 T20S.