

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional lines, T. 20 S., R. 7 W.

CHAINS

The cor. falls on a spur sloping NE.

Ascend 90 ft. along N. slope, changing to NE. slope.

12.40 Top of ascent, slopes N.; desc. 70 ft. over steep NW. slope.

14.00 Bottom of descent, slopes N.; asc. 20 ft. over NE. slope.

15.65 Top of ascent, slopes N.; desc. 130 ft. over steep NW. slope.

20.40 Dry bed of creek, 4 lks. wide, course N., curving to NE.; asc. 8 ft. over creek bottom.

21.00 Dry bed of creek, 4 lks. wide, course NE.; asc. 365 ft. over steep rocky SE. slope.

39.17 The $\frac{1}{4}$ sec. cor. of secs. 30 and 31, monumented with the original sandstone, 18 x 10 x 6 ins., firmly set, 10 ins. in the ground, mkd. $\frac{1}{4}$ on S. face, from which the remaining original bearing tree:

An uprooted and burned fir, 10 ins. diam., bears N. 29° W., 22 lks dist., with scribe marks BT visible on remaining portion of opened blaze.

At the corner point

Set an iron post, 28 ins., long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 20 S R 7 W
 $\frac{1}{4}$ S 30
 $\frac{1}{4}$ S 31
 1966

from which new bearing trees

A burned fir, 53 ins., diam., bears N. 24° E., 76 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S30 BT.

A burned fir, 28 ins. diam., bears S. 41° W., 61 lks. dist., mkd. $\frac{1}{4}$ S31 BT.

Deposit the original cor. stone and set a steel fence post alongside the iron post.

S. 89° 34' W., beginning new measurement.

Ascend 50 ft. over rocky SE. slope.

1.40 Rocky point, slopes S.; asc. 130 ft. over rocky S. slope, changing to SE. slope.

11.20 Intersect the E. bdy. of sec. 25, T. 20 S., R. 8 W., and true point for the closing cor. of secs. 30 and 31.

Set an iron post, 24 ins. long, 1 in. diam., 5 ins. in drill hole in solid sandstone 12 ins. below the surface of the ground, with brass cap mkd.

T 20 S | T 20 S
 R 8 W | S 30 CC
 S 25 | S 31
 | R 7 W
 1966

Deposit a quart jar at the base and set a steel fence post alongside the iron post.