

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 20 S., R. 7 W.

CHAINS

From this point the cor. of secs. 25 and 36 only, T. 20 S., R. 8 W., bears S. 1° 07' W., 17.71 chs. dist.

From this same point the original closing cor. of secs. 30 and 31, bears S. 89° 34' W., 0.015 chs. dist., determined at record bearing and distance from the remaining original cor. accessories:

A burned fir, 40 ins. diam., bears S. 33° E., 25 lks. dist., mkd. with a healed blaze.

A burned fir snag, 15 ins. diam., bears N. 85° W., 32 lks. dist., with burned out blaze, no scribe marks visible.

A sandstone in place, 20 x 20 x 4 ins., above ground, bears N. 80° W., 6 lks. dist., with chisel marks WC plainly visible.

and a bearing tree reported by Tillman in 1950,

A burned fir, 48 ins. diam., bears N. 3¼° E., 233½ lks. dist., mkd. with a burned out blaze, no scribe marks visible. (Record distance, 226 lks.)

Land, mountainous.

Soil, rocky clay with sandstone outcroppings.

Timber, burned fir, cedar, hemlock, maple, alder, dogwood, and yew; undergrowth, burned off except for patches of vine maple, salmonberry, huckleberry, salal, and fern. This mile is located in the Oxbow Burn.

From the cor. of secs. 29, 30, 31 and 32.

N. 0° 05' E., bet. secs. 29 and 30.

Descend 5 ft. over N. slope, through burned timber and patches of dense undergrowth.

0.50 Dry bed of creek; 4 lks. wide, course N. from SW.; desc. 6 ft. along creek bed.

1.40 Leave creek bed, course N. 30° E.; desc. 35 ft. over creek bottom.

4.13 Dry bed of Hardenbrook Creek, 10 lks. wide, course E.; asc. 420 ft. over steep S. slope.

14.50 Spur, slopes SE.; asc. 60 ft. over SE. slope.

17.10 Top of ascent, slopes E.; desc. 100 ft. over steep NE. slope.

19.20 Head of ravine, drains E.; asc. 14 ft. along steep rocky E. slope.

20.42 Point for the S 1/16 sec. cor. of secs. 29 and 30.

Set an iron post, 28 ins. long, 1 in. diam., 6 ins. in drill hole in solid sandstone 18 ins. below the surface of the ground, with brass cap mkd.

S 1/16
S 30 | S 29
1966

from which

A burned fir, 43 ins. diam., bears S. 89½° E., 58 lks. dist., mkd. S 1/16 S29 BT.

A burned fir, 20 ins. diam., bears S. 57½° W., 23½ lks. dist., mkd. S 1/16 S30 BT.