

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 20 S., R. 7 W.

CHAINS

Set a steel fence post alongside the iron post.

Ascend 14 ft. along steep rocky E. slope.

21.50 Top of ascent, slopes E.; desc. 130 ft. over NE. slope.


25.60 Ravine, drains SE.; asc. 95 ft. over SE. slope.

27.65 Top of ascent, slopes E.; desc. 65 ft. over NE. slope.

34.45 Wet ravine, drain S. 30° E.; asc. 330 ft. over steep rocky SW. slope

40.84 Point for the 1/4 sec. cor. of secs. 29 and 30, at proportionate dist. there is no remaining evidence of the orig. cor.

Set an iron post, 28 ins. long, 2 1/2 ins diam., 24 ins. in the ground, with brass cap mkd.



from which

A burned fir, 20 ins., diam., bears S. 39 1/2° E., 142 lks. dist., mkd. 1/4 S29 BT.

A burned fir, 62 ins. diam., bears N. 75° W., 59 lks. dist., mkd. 1/4 S30 BT.

Set a steel fence post alongside the iron post.

Ascend 70 ft. over S. slope.


43.00 Spur ridge and abandoned trail, bears NW. and SE.; desc. 375 ft. over steep NE. slope.

53.15 Wet ravine, drains N. 85° E.; asc. 270 ft. over steep SE. slope.

58.60 Spur, slopes E.; desc. 60 ft. over NE. slope.

61.26 Point for the N 1/16 sec. cor. of secs. 29 and 30.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

A burned fir, 40 ins. diam., bears S. 36° E., 89 lks. dist., mkd. N 1/16 S29 BT.

A burned fir, 65 ins. diam., bears S. 78° W., 91 1/2 lks. dist., mkd. N 1/16 S30 BT.

Set a steel fence post alongside the iron post.

The cor. falls in head of ravine, drains S. 75° E.

Ascend 245 ft. over steep rocky SE. slope.