

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 20 S., R. 7 W.

CHAINS

- 67.50 Ridge, dividing Yellow Creek and South Sister Creek drainages, bears NE. and SW.; desc. 190 ft. over NW. slope.
- 73.00 Bottom of descent, slopes NW.; asc. 15 ft. along W. slope.
- 75.50 Top of ascent, slopes W.; desc. 45 ft. over NW. slope.
- 78.00 Spur, slopes NW.; desc. 160 ft. over steep rocky NW. slope.
- 81.68 The cor. of secs. 19, 20, 29, and 30, perpetuated and recorded by Wilford N. Haines, Registered Surveyor No. 239, in 1961, monumented with a T-iron, 1 in. by 1 in., protruding 6 ins. above the ground, firmly set, with 1 in. diam, cap mkd. WILFORD HAINES 239 SURVEY POINT DRAIN, OREGON, and subsequently perpetuated and recorded by the Douglas County Surveyor in February 1966, monumented with an iron post, 1½ in. diam., protruding 8 ins. above the ground, firmly set, with 2¼ inch brass cap mkd.

County Surveyors Office

T 20 S
 S 19 | S 20
 S 30 | S 29
 R 7 W
 1966

from which the remaining orig. bearing trees

A burned fir, 48 ins. diam., bears N. 45° E., 27 lks. dist., with burned out blaze, no scribe marks visible.

An uprooted fir, 60 ins. diam., bears S. 75½° E., 17 lks. dist., with burned out blaze, no scribe marks visible. (Record bearing, S. 5½° E.)

A fir stump hole, bears S. 30½° W., 23 lks. dist. and a bearing object mkd. by Haines in 1961.

A vertical rock outcropping, 3 ft. high, 10 ft. long, bears S. 68¼° E., 26½ lks. dist., with chisel marks S29 X BO. The X BO. The X has a 1 in. diam. brass cap, which is attached with a nail, centered over it.

and bearing trees mkd. by the County Surveyor in February 1966

A burned maple, 11 ins. diam., bears S. 40½° E., 39½ lks. dist., with scribe marks T20S R7W S29 CS BT visible on burned blaze.

A burned hemlock, 6 ins. diam., bears S. 11° W., 50½ lks. dist., with scribe marks T20S R7W S30 CS BT visible on burned blaze.

and new bearing trees

A sawed and burned fir stump, 45 ins. diam., bears S. 35¾° E., 184½ lks. dist., mkd. T20S R7W S29 BT.

A sawed and burned fir stump, 40 ins. diam., bears N. 13½° W., 93½ lks. dist., mkd. T20S R7W S19 BT.

Set a steel fence post alongside the iron post.

Land, mountainous.

Soil, rocky clay with sandstone outcroppings.

Timber, burned fir, cedar, hemlock, maple, alder, dogwood, and yew; undergrowth, burned off except for patches of vine maple, salmonberry huckleberry, salal, and fern. This mile is located in the Osbow Burn.

S. 89° 17' W., bet. secs. 19 and 30.

Descend 50 ft. over NW. slope, changing to rocky N. slope, along S. edge of logged area, through burned timber void of undergrowth.