

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 20 S., R. 7 W.

## CHAINS

3.25 Spur, slopes NW.; desc. 265 ft. over steep NW. slope.

9.00 Creek, 1 lk. wide, course N. 20° E.; asc. 475 ft. over steep E. slope.

19.40 Point for the E 1/16 sec. cor. of secs. 19 and 30.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16  $\frac{S 19}{S 30}$ 

1966

from which

A sawed and burned fir stump, 47 ins. diam., bears N. 9° E., 37 lks. dist., mkd. E 1/16 S19 BT.

A burned fir, 35 ins. diam., bears South, 34 lks. dist., mkd. E 1/16 S30 BT.

Deposit broken glass at the base and set a steel fence post alongside the iron post.

Ascend 160 ft. over SE. slope.

25.70 Spur, slopes NE.; also SW. cor. of logged area, edges bear NE. and E.; desc. 134 ft. over NW. slope.

30.65 Bottom of descent, slopes N.; asc. 45 ft. over NE. slope.

33.50 Spur, slopes N. 55° W.; desc. 155 ft. over W. slope, changing to SW slope.

38.80 The ¼ sec. cor. of secs. 19 and 30, monumented with the original burned and shattered sandstone, size indeterminate, with faint chisel marks visible, from which the original bearing trees:

A burned fir, 31 ins. diam., bears N. 28° W., 42 lks. dist., with a portion of original scribe marks visible on burned out blaze and rescribed ¼ S19 BT on new blaze.

A burned fir, 50 ins. diam., bears S. 26° W., 6 lks. dist., with a portion of original scribe marks visible on burned out blaze and rescribed ¼ S30 BT on new blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 20 S R 7 W

¼  $\frac{S 19}{S 30}$ 

1966

Deposit the original corner stone alongside and a quart jar at the base of the iron post.

Set a steel fence post alongside the iron post.

No live bearing trees available within limits.

N. 89° 50' W., beginning new measurement.

Descend 295 ft. over SW. slope.