

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 20 S., R. 7 W.

CHAINS

10.03 Intersect the E. bdy. of sec 24, T. 20 S., R. 8 W., at the orig. closing cor. of secs. 19 and 30, previously described.

From this point, the cor. of secs. 24 and 25 only, T. 20 S., R. 8 W., bears S. 1° 14' W., 19.39 chs. dist.

Land, mountainous.

Soil, rocky clay.

Timber, burned fir, hemlock, cedar, maple, dogwood, and chinquapin; undergrowth, burned off except for scattering patches of salal and fern. This mile is located in the Oxbow Burn.

To complete the survey of sec. 30, I return to the $\frac{1}{4}$ sec. cor. of sec. 25 only, on the E. Bdy. of T. 20 S., R. 8 W., and run

N. 1° 13' E., along the W. bdy. of sec. 30.

18.60 Point for the $\frac{1}{4}$ sec. cor. of sec. 30 only, at midpoint latitudinally on the W. bdy. of sec. 30.

Set an iron post, 15 ins. long, 1 in. diam., 5 ins. in drill hole in solid sandstone, with brass cap mkd.

T 20 S
$\frac{1}{4}$ S 30
R 7 W
1966

from which

A sandstone boulder, 10 x 6 x 10 ft. above ground, bears N. 63 $\frac{1}{2}$ ° E., 40 lks. dist., mkd. XBO on W. face.

A sandstone boulder, 8 x 5 x 6 ft. above ground, bears S. 19 $\frac{1}{2}$ ° E., 59 lks. dist., mkd. XBO on N. face.

Set a steel fence post alongside the iron post.

The following field notes describe the remonumentation of certain original corner points in T. 20 S., R. 7 W., as provided for in the General Special Instructions, Group 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories, Followed by Remonumentation of Corner Points, with New Accessories when Needed".

Remonumentation of Certain Original Corner Points, T. 20 S., R. 7 W., Willamette Meridian, Oregon

(Remonumenting corners established by Thomas E. Todd, in 1891)

The cor. of secs. 2, 3, 10, and 11, determined at record distance from the remaining original bearing trees:

A burned fir, 58 ins. diam., bears S. 54° W., 19 lks. dist., with scribe marks R7W S10 visible on partially opened blaze. (Record, S. 61 $\frac{1}{2}$ ° W.)

A burned cedar, 22 ins. diam., bears N. 69° W., 10 lks. dist., with burned out blaze, no marks visible. Rescribed T20S R7W S3 ET on new blaze. (Record, N. 29 $\frac{1}{2}$ ° W.)

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.