

## County Surveyor's Record, Douglas County, Oregon

T. 20 S., R. 7 W.

CHAINS

$$\begin{array}{r} T\ 20\ S\ R\ 7\ W \\ \hline S\ 3\ | S\ 2 \\ \hline S\ 10\ | S\ 11 \\ 1967 \end{array}$$

from which new bearing trees

A maple, 31 ins. diam., bears N. 62° E., 243 lks. dist., mkd. T20S R7W S2 BT.

A cedar, 27 ins. diam., bears S 1° E., 71½ lks. dist., mkd. T20S R7W S11 BT.

Set a steel fence post alongside the iron post.

The ¼ sec. cor. of secs. 2 and 11, monumented with the original sandstone, 18 x 16 x 6 ins., firmly set, 8 ins. in the ground, with chisel marks ¼ on the N. face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} T\ 20\ S\ R\ 7\ W \\ \hline \frac{1}{4} S\ 2 \\ \hline \frac{1}{4} S\ 11 \\ 1967 \end{array}$$

from which new bearing trees

A burned fir, 23 ins. diam., bears N. 23° E., 43 lks. dist., mkd. ¼ S2 BT.

A burned cedar, 27 ins. diam., bears S. 59° W., 48 lks. dist., mkd. ¼ S11 BT.

Set a steel fence post alongside the iron post.

The ¼ sec. cor. of secs. 2 and 3, determined at record bearing and distance from the original NE. bearing tree and substantiated by the original SW. bearing tree:

A sawed fir stump, 35 ins. diam., bears N. 29° E., 50 lks. dist., with a healed blaze.

An uprooted fir, 50 ins. diam., bears S. 46° W., 27 lks. dist., with a healed blaze. (Record, 23 lks.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \\ S\ 3\ | S\ 2 \\ \hline T\ 20\ S\ R\ 7\ W \\ 1967 \end{array}$$

from which a new bearing tree

A fir, 8 ins. diam., bears N. 24½° W., 162 lks. dist., mkd. ¼ S3 BT.

Set a steel fence post alongside the iron post.