

## County Surveyor's Record, Douglas County, Oregon

Remonumentation of Certain Original Corner Points,  
T. 20 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

The  $\frac{1}{4}$  sec. cor. of secs. 15 and 16, determined at record bearing and distance from the remaining original bearing tree:

A stump hole, bears S.  $13^{\circ}$  E., 36 lks. dist., with an uprooted and burned fir, 22 ins. diam., lying downhill, with scribe marks  $\frac{1}{4}$  visible on partially open blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 20 S R 7 W  
 $\frac{1}{4}$   
 S 16 | S 15  
 1966

from which new bearing trees

A burned maple, 12 ins. diam., bears N.  $10^{\circ}$  E., 21 lks. dist., mkd.  $\frac{1}{4}$  S15 BT.

A burned fir, 53 ins. diam., bears S.  $61^{\circ}$  W., 111 lks. dist., mkd.  $\frac{1}{4}$  S16 BT.

Set a steel fence post alongside the iron post.

The cor. of secs. 9, 10, 15, and 16, monumented with the original broken sandstone, 18 x 12 x 8 ins. firmly set, 12 ins. in the ground mkd. with 4 grooves on S. face and a cross on the top, from which the remaining original bearing trees:

A burned cedar snag, 20 ins. diam., bears N.  $32^{\circ}$  E., 44 lks. dist., with no marks remaining.

A burned fir, 42 ins. diam., bears S.  $12^{\circ}$  E., 74 lks. dist., with burned out blaze, no scribe marks visible. (Record, S.  $10^{\circ}$  E., 80 lks. dist.)

A burned cedar stump, 20 ins. diam., bears N.  $15^{\circ}$  W., 34 lks. dist., no marks remaining. (Record distance, 37 lks.)

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 20 S R 7 W  
 S 9 | S 10  
 S 16 | S 15  
 1966

from which new bearing trees

A burned maple, 17 ins. diam., bears N.  $52\frac{1}{2}^{\circ}$  E., 88 lks. dist., mkd. T20S R7W S10 BT.

A burned maple, 21 ins. diam., bears S.  $32^{\circ}$  W.,  $27\frac{1}{2}$  lks. dist., mkd. T20S R7W S16 BT.

A burned and hollow cedar, 45 ins. diam., bears N.  $42^{\circ}$  W., 85 lks. dist., mkd. T20S R7W S9 BT.

Deposit the original cor. stone and set a steel fence post alongside the iron post.