

County Surveyor's Record, Douglas County, Oregon

Remonumentation of Certain Original Corner Points,
T. 20 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 9 and 10, monumented by the Oregon State Board of Forestry, in 1967, with an iron post, $1\frac{1}{2}$ ins. diam., firmly set, projecting 4 ins. above the ground, with bronze cap mkd.

OREGON STATE BOARD OF FORESTRY
S 9 | S 10
1967

from which bearing trees by Oregon State Board of Forestry

A sawed and burned fir stump, 25 ins. diam., bears S 44° E., 9 lks. dist., with scribe marks $\frac{1}{4}$ S9 BT visible on open blaze.

A burned fir, 30 ins diam., bears N. 89° W., 32 lks. dist., with scribe marks $\frac{1}{4}$ S10 BT RS 563 visible on open blaze.

and a new bearing tree

A burned fir, 12 ins. diam., bears S. $59\frac{1}{2}^{\circ}$ W., $54\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S9 BT.

Set a steel fence post and a 4 in. square, 4 ft. long, white wooden post alongside the iron post.

The cor. of secs. 3, 4, 9, and 10, monumented by the Oregon State Board of Forestry, in 1967, with an iron post, $1\frac{1}{2}$ ins. diam., firmly set, projecting 5 ins. above the ground, with bronze cap mkd.

OREGON STATE BOARD OF FORESTRY
T 20 S R 7 W
S 4 | S 3
S 9 | S 10
1967

from which the original bearing trees

A burned fir, 40 ins. diam., bears N. 76° E., 25 lks. dist., with scribe mark T visible on partially opened blaze. (Record, 75 lks.)

A burned fir, 30 ins. diam., bears S. 12° E., 54 lks. dist., with a burned blaze.

A burned fir, 31 ins diam., bears S. 87° W., 54 lks. dist., with scribe marks W S9 visible on partially opened blaze.

An uprooted fir, 34 ins. diam., bears N. 19° W., 8 lks. dist., with healed blaze.

and bearing trees by Oregon State Board of Forestry

A burned fir, 45 ins. diam., bears N. 27° E., 45 lks. dist., with scribe marks T20S R7W S3 visible on unhealed blaze.

A burned fir, 45 ins. diam., bears S. 66° E., $77\frac{1}{2}$ lks. dist., with scribe marks T20S R7W S10 BT visible on unhealed blaze.

A burned fir, 34 ins. diam., bears N. 59° W., 61 lks. dist., with scribe marks T20S R7W S4 BT visible on unhealed blaze.

No other suitable trees available within limits.

Set a steel fence post alongside the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 3 and 10, monumented by the Oregon State Board of Forestry, in 1967, with an iron post, $1\frac{1}{2}$ ins. diam., firmly set, projecting 4 ins. above the ground, with bronze cap mkd.