

## County Surveyor's Record, Douglas County, Oregon

Remonumentation of Certain Original Corner Points,  
T. 20 S., R. 7 W., Willamette Meridian, Oregon

## CHAINS

The  $\frac{1}{4}$  sec. cor. of secs. 16 and 17, monumented with the original sandstone, 17 x 13 x 4 ins., firmly set, projecting 8 ins. above ground, marked  $\frac{1}{4}$  on the W. face; alongside of which is a County Surveyor's iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

## COUNTY SURVEY OFFICE

T 20 S  
 $\frac{1}{4}$  S 17 | S 16  
R 7 W  
1966

from which the original bearing trees

A burned fir snag, 32 ins. diam., bears N.  $61^{\circ}$  E., 14 lks. dist., with burned blaze, no marks visible.

A burned fir, 27 ins diam., bears S.  $80^{\circ}$  W., 7 lks. dist., with a healed blaze.

and bearing trees mkd. by the County Surveyor

A burned fir, 50 ins. diam., bears N.  $37\frac{1}{2}^{\circ}$  E., 44 lks. dist., with scribe marks  $\frac{1}{4}$  S16 CS BT visible on open blaze.

A burned fir, 50 ins. diam., bears S.  $29^{\circ}$  W., 39 lks. dist., with scribe marks  $\frac{1}{4}$  S17 CS BT visible on open blaze.

Set a steel fence post alongside the iron post.

The cor. of secs. 8, 9, 16, and 17, determined at record bearing and distance from the remains of the original bearing trees:

An uprooted and burned fir, 50 ins. diam., bears N.  $64^{\circ}$  E., 17 lks. dist., no marks visible.

A burned fir snag, 28 ins. diam., bears S.  $38^{\circ}$  E., 9 lks. dist. with burned blaze, no scribe marks visible. Rescribed T20S R7W S16 BT on new blaze.

A stump hole, bears S.  $10^{\circ}$  W., 17 lks. dist.

An uprooted and burned fir, 43 ins. diam., bears N.  $29^{\circ}$  W., 55 lks. dist., with scribe marks S8 visible on partially opened blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins diam., 24 ins. in the ground, with brass cap mkd.

T 20 S R 7 W  
S 8 | S 9  
S 17 | S 16  
1967

from which new bearing trees

A sawed and burned fir stump, 70 ins. diam., bears S.  $48^{\circ}$  W.,  $60\frac{1}{2}$  lks. dist., mkd T20S R7W S17 BT.

A sawed and burned fir stump, 36 ins. diam., bears N.  $24\frac{1}{2}^{\circ}$  W., 64 lks. dist., mkd T20S R7W S8 BT.

No other suitable trees available within limits.

Set a steel fence post alongside the iron post.