

## County Surveyor's Record, Douglas County, Oregon

Remonumentation of Certain Original Corner Points,  
T. 20 S., R. 7.W., Willamette Meridian, Oregon

## CHAINS

The  $\frac{1}{4}$  sec. cor. of secs. 8 and 9, falls on the edge of a rock outcrop, 40 ft. long, 7 ft. high, bears N.  $46^\circ$  E., mkd. with a faint cross at the exact cor. point, alongside of which is marked  $\frac{1}{4}$ , from which the remaining original bearing tree:

A rotted fir stump, 12 ins. diam., bears N.  $26^\circ$  E., 10 lks. dist., no marks visible.

At the corner point

Set an iron post, 8 ins. long, 1 in. diam., 7 ins. in a drill hole in solid rock, with brass cap mkd.

T 20 S R 7 W  
 $\frac{1}{4}$   
 S 8 | S 9  
 1967

from which new bearing trees

A sawed fir stump, 23 ins. diam., bears N.  $27^\circ$  E.,  $41\frac{1}{2}$  lks. dist., mkd.  $\frac{1}{4}$  S9 BT.

A sawed fir stump, 27 ins., diam., bears S.  $43^\circ$  W.,  $85\frac{1}{2}$  lks. dist., mkd.  $\frac{1}{4}$  S8 BT.

Set a steel fence post alongside the iron post.

The cor. of secs. 4, 5, 8, and 9, determined at record distance from the remaining original bearing trees:

A hemlock snag, 33 ins. diam., bears S.  $58\frac{1}{2}^\circ$  W., 66 lks. dist., with fragmentary scribe marks visible on partially opened blaze. (Record, S.  $64^\circ$  W.)

A maple snag, 23 ins. diam., bears N.  $59^\circ$  W., 47 lks. dist., with fragmentary scribe marks visible on partially opened blaze. (Record, N.  $46^\circ$  W.)

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground with brass cap mkd.

T 20 S R 7 W  
 S 5 | S 4  
 S 8 | S 9  
 1967

from which new bearing trees

A sawed and burned fir stump, 50 ins. diam., bears N.  $23\frac{1}{2}^\circ$  E., 63 lks. dist., mkd. T20S R7W S4 BT.

A burned cedar, 50 ins. diam., bears S.  $28\frac{1}{2}^\circ$  W., 85 lks. dist., mkd. T20S R7W S8 BT.

A burned fir, 45 ins. diam., bears N.  $71^\circ$  W., 41 lks. dist., mkd. T20S R7W S5 BT.

No other suitable tree available within limits.

Set a steel fence post alongside the iron post.