

County Surveyor's Record, Douglas County, Oregon

Remonumentation of Certain Original Corner Points,
T. 20 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

(Rehabilitating a corner established by Thomas E. Todd, in 1891,
and remonumented by Floyd A. Brooks, in 1960)

The $\frac{1}{4}$ sec. cor. of secs. 19 and 20, monumented with an iron post,
2 $\frac{1}{2}$ ins., diam., firmly set, projecting 4 ins. above the ground,
with brass cap mkd.

$$\begin{array}{ccc} & \frac{1}{4} & \\ & | & \\ S\ 19 & & S\ 20 \\ T\ 20\ S\ R\ 7\ W & & \\ & 1960 & \end{array}$$

from which original bearing trees

A fir root crown, 36 ins. diam., bears N. 86° E., 32 lks.
dist., no marks visible.

A fir root crown, 35 ins. diam., bears N. 43° W., 21 lks. dist,
no marks visible.

and a bearing tree mkd. by Brooks in 1960

A burned fir snag, 15 ins. diam., bears S. 57° E., 148 lks.
dist., with burned original face, no marks visible. Remkd.
 $\frac{1}{4}$ S20 CS BT on new blaze by the County Surveyor in 1966.

and a bearing tree mkd. by the County Surveyor in 1966

A sawed and burned fir stump, 42 ins. diam., bears N. 74° W.,
44 lks. dist., with scribe marks $\frac{1}{4}$ S19 CS BT visible on open
blaze.

and a new bearing tree

A burned maple snag, 15 ins. diam., bears N. 75° E., 121 lks.
dist., mkd $\frac{1}{4}$ S20 BT.

Set a steel fence post alongside the iron post.

(Remonumenting Corners Established by Thomas E. Todd, in 1891)

The ocr. of secs. 17, 18, 19, and 20, perpetuated and recorded by
Wilforn N. Haines, Registered Surveyor No. 239, in 1961, monumented
with a 1 in. x 1 in. T-iron, 36 ins. long, with aluminum disc. mkd.
WIFLORD N. HAINES DRAIN OREGON 239 SURVEY POINT, and subsequently
perpetuated and recorded by the Couglas County Surveyor in 1966,
and monumented with an iron post, 1 in. diam., firmly set, project-
ing 8 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

$$\begin{array}{ccc} T\ 20\ S & & \\ S\ 18 & | & S\ 17 \\ S\ 19 & | & S\ 20 \\ R\ 7\ W & & \\ & & 1966 \end{array}$$

from which original bearing trees

An uprooted maple, 16 ins. diam., bears N. 26° E., 11 lks.
dist., with healed blaze.

A sawed and burned fir stump, 42 ins. diam., bears S. 52° E.,
81 lks. dist., with healed blaze and rescribed T20S R 7W
S20 CS BT on new blaze.

A sawed and burned fir stump, 52 ins. diam., bears S. 14° W.,
30 lks. dist., with illegible scribe marks on partially open-
ed blaze, and rescribed T20S R7W CS BT on new blaze. (record,
S. 26° W., 27 lks.)