

County Surveyor's Record, Douglas County, Oregon

Monumentation of Certain Original Corner Points,
T. 20 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

and new bearing trees

A burned fir snag, 32 ins. diam., bears N. 60° E., 111 lks. dist., mkd. T20S R7W S17 BT.

A burned fir snag, 45 ins. diam., bears N. 19° W., 111 lks. dist., mkd. T20S R7W S18 BT.

Set a steel fence post alongside the iron post.

The cor. of secs. 7, 8, 17 and 18, monumented with the original sandstone, 20 x 16 x 5 ins., firmly set, 16 ins. in the ground, mkd. with 5 notches on the E. edge, from which the remaining orig. bearing trees:

A burned maple shell, 40 ins. diam., bears S. 28° E., 100 lks. dist., with healed blaze. (Record, S. 24° E.)

A burned cedar, 32 ins. diam., bears S. 86° W., 108 lks. dist. with a burned blaze, no scribe marks visible. Rescribed T20S R7W S18 BT on new blaze. (Record, S. 80° W., 118 lks.)

At the corner point

Set an iron post 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.

T 20 S R 7 W
S 7 S 8
S 18 S 17
1967

from which new bearing trees

A sawed and burned cedar stump, 85 ins. diam., bears N. 70° E., 65 lks. dist., mkd T20S R7W S8 BT.

A burned double maple, 58 ins. diam., bears S. 42½° E., 128 lks. dist., mkd. T20S R7W S17 BT.

No other suitable trees available within limits.

Deposit the original stone and set a steel fence post alongside the iron post.

The cor. falls 37 lks. north of South Sister Creek, 10 lks. wide, course SW.

The cor. of secs. 5, 6, 7 and 8, monumented with the broken orig. sandstone, 12 x 8 x 3 ins., lying on top of the ground, mkd. with 5 notches on E. edge, from which the original bearing trees.

An uprooted and burned maple stump, 10 ins. diam., bears N. 60° E., 53 lks. dist., no marks visible. (Record and slope distance, 56 lks.)

A burned and dead fir, 27 ins. diam., bears S. 84° E., 49 lks. dist., mkd. with a healed blaze.

A burned and dead fir, 32 ins. diam., bears S. 35° W., 10 lks. dist., with scribe mark S visible on partially opened blaze. (Record bearing S. 45° W.)

An uprooted and burned maple stump, 8 ins. diam., bears N. 62° E., 42 lks. dist., no marks visible.