

## County Surveyor's Record, Douglas County, Oregon

Remonumentation of Certain Original Corner Points,  
T. 20 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 20 S R 7 W  
S 6 | S 5  
S 7 | S 8  
1967

from which new bearing trees

A sawed and burned fir stump, 55 ins. diam., bears N.  $21\frac{1}{2}^\circ$  E., 66 lks. dist., mkd. T20S R7W S5 BT.

A sawed and burned fir stump, 40 ins. diam., bears N.  $28\frac{1}{2}^\circ$  W.,  $92\frac{1}{2}$  lks. dist., mkd. T20S R7W S6 BT.

Deposit the cor. stone and set a steel fence post alongside the iron post.

From this point electronic survey control point, ABC 2, established during the Aerial Electronic Cadastral Resurvey in the Oxbow Ridge Fire Area, in 1967, bears N.  $50^\circ 43'$  E., 7.66 chs. dist., monumented with an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 25 ins. in the ground, with brass cap mkd.

ABC 2  
+  
1967

from which

A sawed and burned fir stump, 52 ins. diam., bears N.  $41^\circ$  E.,  $102\frac{1}{2}$  lks. dist., mkd. ABC 2 BT.

A sawed and burned fir stump, 55 ins. diam., bears S.  $14^\circ$  W.,  $71\frac{1}{2}$  lks. dist., mkd. ABC 2 BT.

The  $\frac{1}{4}$  sec cor. of secs. 6 and 7, determined at record bearing and distance from the original bearing trees:

A burned and dead fir, 40 ins. diam., bears N.  $20^\circ$  E., 11 lks. dist., with scribe marks  $\frac{1}{4}$  S BT visible on opened blaze.

A burned and dead fir, 32 ins. diam., bears S.  $31^\circ$  W., 12 lks. dist., mkd. with a healed blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 20 S R 7 W  
 $\frac{1}{4}$  S 6  
S 7  
1967

Set a steel fence post alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 5 and 6, determined at record bearing and distance from the original bearing trees:

A burned and sawed fir stump, 45 ins. diam., bears S.  $89^\circ$  E., 55 lks. dist., with scribe marks  $\frac{1}{4}$  visible on partially opened blaze.

A burned and sawed fir stump, 45 ins. diam., bears S.  $47^\circ$  W., 45 lks. dist., with a healed blaze.