

County Surveyor's Record, Douglas County, Oregon

T. 21 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

The history of the surveys of township 21 south, range 7 west, Willamette Meridian, Oregon, pertaining to this resurvey is as follows:

The subdivisional lines were surveyed by William P. Wright in 1884 as shown on the official plat of survey approved February 25, 1885. In 1954, Thomas A. Tillman dependently resurveyed the north four miles of the west boundary as shown on the official plat of survey accepted April 14, 1960. Floyd A. Brooks and James E. Jelley dependently resurveyed a portion of the subdivisional lines in 1964 as shown on the official plat of survey accepted August 20, 1965.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions, lost corners were reestablished and remonumented at proportionate positions, based on the original record. The retrace-ment data were thoroughly verified and only true line field notes are given herein. Only those lines bounding, or crossing, public lands were blazed.

The resurvey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated August 31, 1967, under group No. 655, Oregon.

The directions of the lines were determined by the solar transit method.

The geographic position of the corner of sections 19, 20, 29, and 30, as scaled from the Elkton Quadrangle Map, prepared by the United States Geological Survey in 1955, as follows:

Latitude 43° 43.3' N. Longitude 123° 33.9' W.

The mean magnetic declination is 20° 00' E.

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon

(Restoring the 1884 survey by William P. Wright)

Beginning at the  $\frac{1}{4}$  sec. cor. of secs. 20 and 29, monumenting with an iron post, 2 $\frac{1}{2}$  ins. diam., firmly set, protruding 5 ins. above ground, with brass cap mkd. and witnessed as described in the official record of the 1964 dependent resurvey.

N. 89° 16' W., bet. secs. 20 and 29, marking and blazing the true line.

Descend 325 fr. over SW. slope, through heavy timber and dense undergrowth.

10.70 Creek, 1 lk. wide, course N. 10° W.; asc. 320 ft. over NE. slope.

19.60 Spur, slopes N. 30° W.; desc. 170 ft. over SW. slope.

23.96 Point for the W 1/16 sec. cor. of secs. 20 and 29.

Set an iron post, 28 ins. long. 2 $\frac{1}{2}$  ins. diam., 21 ins. in the ground, with brass cap marked

S 20  
W 1/16 S 29  
1967