

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 21 S., R. 7 W.

CHAINS	
	<p>from which</p> <p>A fir, 8 ins. diam., bears S. $62\frac{1}{2}^{\circ}$ E., 22 lks. dist., mkd. S $\frac{1}{16}$ S20 BT.</p> <p>A fir, 8 ins. diam., bears S. 30° W., 7 lks. dist., mkd. S $\frac{1}{16}$ S19 BT.</p> <p>Ascend 90 ft. over S. slope.</p>
27.60	Spur, slopes S. 60° W.; desc. 115 ft. over NW. slope.
33.70	Creek, 2 lks. wide, course S. 20° W.; asc. 155 ft. over SE. slope.
37.16	<p>The $\frac{1}{4}$ sec. cor. of secs. 19 and 20, determined at record bearing and distance from the remains of the original bearing trees:</p> <p>A stump hole, bears N. 35° E., 56 lks. dist.</p> <p>A fir snag, 60 ins. diam., bears N. 78° W., 20 lks. dist., mkd. $\frac{1}{4}$ S BT on bark blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 21 S R 7 W $\frac{1}{4}$ S 19 S 20 1967</p>
	<p>from which</p> <p>A fir, 8 ins. diam., bears S. 36° E., 4 lks. dist., mkd. $\frac{1}{4}$ S20 BT.</p> <p>A fir, 12 ins. diam., bears N. $19\frac{1}{2}^{\circ}$ W., $31\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S19 BT.</p> <hr/> <p>N. 0° 31' E., beginning new measurement.</p> <p>Ascend 530 ft. over SE. slope, changing to S. slope.</p>
28.15	Dirt road, 15 lks. wide, bears N. 70° W. and S. 70° E.
29.60	Ridge, bears N. 60° W. and S. 60° E.; desc. 240 ft. over NE. slope.
37.00	<p>The cor. of secs. 17, 18, 19 and 20, determined from the remains of the original bearing trees:</p> <p>A rotted fir stump, 35 ins. diam., bears N. 88° E., 62 lks. dist., no marks remaining.</p> <p>A rotted fir stump, 12 ins. diam., bears S. 42° E., 31 lks. dist., with old axe marks visible on the bark. (Record, S. 37° E., 36 lks. dist.)</p> <p>A rotted fir stump, 37 ins. diam., bears S. 28° W., 48 lks. dist., no marks remaining. (Record and slope distance, 56 lks.)</p> <p>A rotted fir stump, 35 ins. diam., bears N. 13° W., 64 lks. dist., no marks remaining.</p> <p>At the corner point.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap marked</p>